

DRAWING INDEX

PROJECT LAYOUT PLAN

COVER SHEET

GENERAL NOTES

TYPICAL SECTION

BORINGS LOGS

KEY SHEET

SITE PLAN

DESCRIPTION

EXISTING CONDITIONS AND DEMOLITION PLANS

STAKING AND GEOMETRY PLANS

DRAINAGE AND GRADING PLANS

CONSTRUCTION DETAILS

PLAN AND PROFILE PLANS

DRAINAGE DETAILS

CROSS SECTIONS

SWPPP PLAN

SWPPP NOTES

MARKING PLAN

MARKING DETAILS

FENCE AND GATE DETAILS

PCC PAVEMENT JOINTS LAYOUT

DRAWING No.

G0.0

G1.1

G1.2

G2.1

G3.1-G3.5

C1.1-C1.2

C2.0

C2.1-C2.5

C3.1-C3.5

C4.1-C4.5

C4.6-C4.9

C4.10-C4.11

C5.1-C5.2

C6.1-C6.11

C7.1

C7.2

C8.1

C9.1-C9.3

C10.1-C10.4


C11.1

OCALA INTERNATIONAL AIRPORT-JIM TAYLOR FIELD OCALA, FLORIDA


CONSTRUCTION PLANS FOR:

NORTH DEVELOPMENT ROAD


FDOT FM NO.: 449858-94-01



BID DOCUMENTS MARCH 2024








PREPARED BY: INFRASTRUCTURE CONSULTING & ENGINEERING 5550 W. IDLEWILD AVENUE, SUITE 115

TAMPA, FL 33634 (813) 330-2701 CERTIFICATE OF AUTHORIZATION NO.: 30862

	REVISIO	NS	
No.	Description	Date	Ву
-			-
			+-
_			+-
-			_
_			4_
		1	




VICINITY MAP


DRAWING INDEX					
DRAWING No.	DESCRIPTION				
UP-01	UTILITY PLAN AND PROFILE (SHEET 1 OF 3)				
UP-02	UTILITY PLAN AND PROFILE (SHEET 2 OF 3)				
UP-03	UTILITY PLAN AND PROFILE (SHEET 3 OF 3)				
UP-04	FORCE MAIN PLAN AND PROFILE				
UP-05	UTILITY KEY PLAN				
UP-06	LIFT STATION PLAN				
UP-07	UTILITY DETAILS (SHEET 1 OF 8)				
UP-08	UTILITY DETAILS (SHEET 2 OF 8)				
UP-09	UTILITY DETAILS (SHEET 3 OF 8)				
UP-10	UTILITY DETAILS (SHEET 4 OF 8)				
UP-11	UTILITY DETAILS (SHEET 5 OF 8)				
UP-12	UTILITY DETAILS (SHEET 6 OF 8)				
UP-13	UTILITY DETAILS (SHEET 7 OF 8)				
UP-14	UTILITY DETAILS (SHEET 8 OF 8)				
UP-15	FDOT STANDARDS DETAILS (SHEET 1 OF 2)				
UP-16	FDOT STANDARDS DETAILS (SHEET 2 OF 2)				
UP-17	LIFT STATION DETAILS				
EL-01	ELECTRICAL SITE PLAN				
EL-02	INSTALLATION DETAILS				

ENGINEER OF RECORD:



PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.





- CONSTRUCTION STANDARDS SHALL BE IN ACCORDANCE WITH THE FDOT 2023-24 STANDARD PLANS, FDOT GREENBOOK 2018
 EDITION AND FDOT STANDARD SPECIFICATIONS (DIVISION II AND III) FOR ROAD AND BRIDGE CONSTRUCTION DATES FY
 2023-24, CITY OF OCALA SPECIFICATIONS AS AMENDED BY CONTRACT DOCUMENTS.
- ALL CONSTRUCTION COVERED IN THESE PLANS SHALL COMPLY WITH THE MATERIAL REQUIREMENTS AND QUALITY CONTROL STANDARDS CONTAINED IN THE CITY OF OCALA STANDARDS SPECIFICATIONS FOR CONSTRUCTION. IN CASE OF CONFLICTS, THE HIERARCHY OF SPECIFICATIONS SHALL BE:
 - 1- CONTRACT DOCUMENTS
 - 2- FDOT STANDARDS SPECIFICATIONS FOR ROADS AND BRIDGE CONSTRUCTION FY 2023-24 (DIVISION II AND III), FDOT 2023-24 STANDARD PLANS FOR ROAD AND BRIDGE CONSTRUCTION
- ALL WORK MUST BE CONDUCTED OUTSIDE THE AOA FENCE. IF ANY WORK IS REQUIRED INSIDE THE AOA FENCE ESCORT SHALL BE REQUIRED.
- 4. THE CONTRACTOR WILL BE RESPONSIBLE FOR THE CLEANUP AND DISPOSAL OF ALL TRASH AND DEBRIS CREATED BY HIS WORK OR PERSONNEL. NO BURNING IS ALLOWED ON SITE. ALL TRASH AND DEBRIS MUST BE DISPOSED OF OFFSITE.
- THE CONTRACTOR SHALL MAKE HIS OWN ARRANGEMENTS FOR ASPHALT AND OR CONCRETE BATCH PLANT LOCATIONS WHICH MUST BE LOCATED OFF AIRPORT PROPERTY.
- 6. THE CONTRACTOR SHALL VISIT SITE TO DETERMINE EXISTING CONDITIONS PRIOR TO SUBMITTING BID. THE CONTRACTOR SHALL REPORT TO THE ENGINEER ANY VARIATIONS FROM THE INFORMATION SHOWN ON THE CONSTRUCTION PLANS.
- APPROVED CUTS IN PAVEMENT OR CONCRETE SHALL BE MADE USING A PAVEMENT SAW, AND SHALL BE PATCHED TO MATCH
 THE EXISTING SURFACE IN A MANNER APPROVED BY THE ENGINEER.
- 8. EXISTING EASEMENTS TO OTHER PROPERTIES SHALL BE MAINTAINED AT ALL TIMES.
- AIRFIELD PAVEMENTS SHALL BE KEPT FREE OF ALL DEBRIS, DIRT, ETC., AT ALL TIMES. ANY SPILLAGE OF EXCAVATION OR OTHER MATERIAL SHALL BE CLEANED UP IMMEDIATELY BY THE CONTRACTOR WITH A MOTOR DRIVEN SWEEPER OR VACUUM AS REQUIRED BY THE ENGINEER. A PROGRAM OF REGULAR AIRFIELD PAVEMENT INSPECTION WILL BE PLANNED BY THE CONTRACTOR, AIRPORT OPERATIONS AND THE OWNER'S REPRESENTATIVE. SWEEPERS ARE TO BE EQUIPPED WITH NON-METALLIC BROOMS.
- 10. ALL NON-PAVED AREAS OUTSIDE THE LIMITS OF CONSTRUCTION WHICH ARE DISTURBED BY THE CONTRACTOR'S OPERATIONS, SUCH AS THE CONTRACTOR'S ACCESS ROAD, STAGING AREA, HAUL ROUTES, ETC., SHALL BE RESTORED TO THEIR ORIGINAL CONDITION AND SODDING AT THE CONTRACTOR'S EXPENSE PER FDOT SPEC 570 UPON COMPLETION OF THE PROJECT
- 11. ANY DAMAGES DONE TO AIRPORT PROPERTY OR UTILITIES (SUCH AS RUNWAY, TAXIWAYS, APRONS, FENCING, EXISTING CABLES) WILL BE REPAIRED BY THE CONTRACTOR TO THE APPROVAL OF THE OWNER OF THE FACILITY IN A SATISFACTORY MANNER. THE CONTRACTOR WILL BEAR ALL COSTS FOR REPAIRS.
- 12. THE CONTRACTOR SHALL MAINTAIN SECURITY WITHIN THE PROJECT SITE AT ALL TIMES. NO UNAUTHORIZED PERSONNEL SHALL BE ALLOWED ON THE SITE.
- 13. THE CONTRACTOR SHALL OBTAIN ALL APPLICABLE PERMITS NECESSARY FOR THE COMPLETION OF THIS PROJECT.
- 14. THE CONTRACTOR IS RESPONSIBLE FOR COMPLIANCE WITH ALL ENVIRONMENTAL RULES AND REGULATIONS OF THE CITY, COUNTY, STATE, ARMY CORPS OF ENGINEERS, AND ANY OTHER JURISDICTIONAL AGENCIES, AND ALL CONDITIONS SET FORTH IN ENVIRONMENTAL PERMITS.
- 15. ALL DISPUTES ARISING FROM THE CONTRACTOR SHALL BE DECIDED BY THE ENGINEER, WHOSE DECISION SHALL BE FINAL,
- 16. ALL DEMOLISHED MATERIALS BECOME THE PROPERTY OF THE CONTRACTOR UNLESS OTHERWISE SHOWN IN THE CONTRACT DOCUMENTS. CONSTRUCTION AND DEMOLITION DEBRIS SHALL BE LEGALLY DISPOSED OF OFF AIRPORT PROPERTY
- 17. THE CONTRACTOR SHALL KEEP A WATER TRUCK ONSITE AT ALL TIMES FOR THE PURPOSE OF CONTROLLING DUST AS REQUIRED BY THE CONTRACT DOCUMENTS.

HAUL ROUTE / STAGING

- 18. THE CONTRACTOR WILL BE RESPONSIBLE FOR THE STORAGE AND SECURITY OF HIS MATERIAL AND EQUIPMENT AND SHALL ERECT STORAGE FACILITIES AND FENCING AS NECESSARY. THE CONTRACTOR'S STORAGE AND STAGING AREA SHALL BE IN THE LOCATION SHOWN ON DRAWING G1.1.
- 19. THE CONTRACTOR'S STAGING AREA(S) AND HAUL ROUTES SHOWN ON THE PLANS ARE GENERAL AND FOR INFORMATIONAL PURPOSES ONLY. THE ACTUAL SIZE AND LOCATION OF STAGING AREAS AND HAUL ROUTES WILL BE APPROVED BY THE OWNER PRIOR TO CONSTRUCTION.
- 20. CONTRACTOR WILL NOT BE ALLOWED TO USE ANY OF THE EXISTING RUNWAYS OR TAXIWAYS AS PART OF THE HAUL ROAD UNLESS SPECIFICALLY AUTHORIZED BY THE OWNER'S REPRESENTATIVE. UNDER NO CIRCUMSTANCE SHALL THE CONTRACTOR CROSS ANY RUNWAY AT ANY TIME WITH CONSTRUCTION VEHICLES OR EQUIPMENT.
- 21. THE EXISTING PAVEMENTS ACCESS ROADS AND HAUL ROUTES MAY NOT BE CAPABLE OF SUPPORTING CERTAIN TYPES OF CONSTRUCTION EQUIPMENT. PRIOR TO BIDDING, THE CONTRACTOR SHALL FULLY SATISFY HIMSELF AS TO THE ABILITY OF THE EXISTING AIRPORT PAVEMENTS TO SATISFACTORILY SUSTAIN THE TYPE OF EQUIPMENT HE PLANS TO USE. CONTRACTOR SHALL SIZE THE EQUIPMENT USED FOR CONSTRUCTION ACCORDINGLY. ANY DAMAGE CAUSED BY HAULING OR ANY OTHER CONSTRUCTION ACTIVITY TO EXISTING PAVEMENT SHALL BE REPAIRED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.

 THE CONTRACTOR IS RESPONSIBLE FOR COORDINATING AND PROVIDING ALL PERMANENT AND TEMPORARY UTILITY CONNECTIONS TO THE STAGING AREA.

QUALITY CONTROL NOTES

- 23. CONTRACTOR SHALL BE REQUIRED TO SUBMIT A QUALITY CONTROL PLAN FOR ALL WORK ITEMS THAT REQUIRE QUALITY CONTROL, QUALITY ASSURANCE, MATERIAL VERIFICATION, DENSITY TESTS, AND ALL FIELD AND LABORATORY TESTS REQUIRED BY THE CONTRACT SPECIFICATIONS. CONTRACTOR SHALL PROVIDE FULL QUALITY CONTROL TESTING BY CERTIFIED FIRMS/INDIVIDUALS.
- 24. WITHIN 10 DAYS OF NOTIFICATION OF INTENT TO AWARD, THE CONTRACTOR SHALL SUBMIT THREE (3) COPIES OF A WRITTEN QUALITY CONTROL PLAN. THE CONTRACTOR SHALL DESIGNATE A QUALITY CONTROL OFFICER RESPONSIBLE FOR THE QUALITY OF CONSTRUCTION AND SHALL INCLUDE AN ORGANIZATIONAL CHART DESIGNATING QUALITY CONTROL RESPONSIBILITIES. THE PLAN SHALL ENCOMPASS A PROGRAM OF QUALITY CONTROL ACTIVITIES FOR THE PROJECT AS A WHOLE, AS WELL AS SPECIFIED PROCEDURES FOR EACH ELEMENT OF WORK.
- 25. FOR EACH MAJOR ELEMENT OF WORK, THE CONTRACTOR SHALL DESCRIBE IN THE QUALITY CONTROL PLAN PRELIMINARY INSPECTION PROCEDURES TO BE ACCOMPLISHED PRIOR TO START UP, PROGRESS INSPECTION PROCEDURES TO MONITOR THE WORK IN PROGRESS, AS WELL AS FINAL INSPECTIONS TO VERIFY ALL TESTS HAVE BEEN PERFORMED AND ARE PASSING, AND ALL CONDITIONS OF THE SPECIFICATIONS HAVE BEEN MET.
- 26. THE CONTRACTOR SHALL BEAR THE COST OF, AND BE RESPONSIBLE FOR ALL "QUALITY CONTROL". OWNER WILL PROVIDE "QUALITY ASSURANCE" TESTING.

PERMITS REQUIRED

REQUIRED PERMITS FOR THIS PROJECT BUT NOT LIMITED TO ARE AS FOLLOWS:

- FEDERAL AVIATION ADMINISTRATION 7460-1 PERMIT
- FDEP NOTICE OF INTENT
- SWFWMD PERMIT
- GOPHER TORTOISE RELOCATION

PAVEMENT MARKINGS

- 1. PAVEMENT SURFACE SHALL BE DRY, NO FOG, RAIN, OR DRIZZLE.
- 2. WIND VELOCITY SHOULD NOT AFFECT UNIFORM APPLICATION.
- CONTRACTOR TO ACCOUNT FOR WIND DRIFT, COVER EXISTING NEAR BUILDINGS, STRUCTURES, ALL NECESSARY LIGHTS
 AND IN-PAVEMENT MARKERS.
- 4. CEASE APPLICATION WHEN EXCESSIVE DUST OR SAND IS BLOWING.
- 5. CEASE APPLICATION WHEN RAIN IS ANTICIPATED WITHIN EIGHT (8) HOURS OF APPLICATION COMPLETION
- 6. THE ATMOSPHERIC TEMPERATURE AND THE PAVEMENT SURFACE TEMPERATURE SHALL BOTH BE ABOVE 60F AND RISING.

SURVEY

- 1. DATE OF FIELD SURVEY: MARCH 23, 2023 BY R.M. BARRINEAU AND ASSOCIATES.
- 2. SUBJECT TO RIGHTS OF WAY, RESTRICTIONS, EASEMENTS AND RESERVATIONS OF RECORD
- 3. UNLESS OTHERWISE SHOWN, UNDERGROUND IMPROVEMENTS NOT LOCATED.
- 4. PUBLIC RECORDS NOT SEARCHED BY R.M. BARRINEAU & ASSOCIATES, INC.
- BEARINGS AND STATE PLANE COORDINATES DEPICTED HEREON ARE GRID, WEST FLORIDA ZONE, NAD-83 (CORS96)
 EPOCH:2002.0000), BASED ON TRIMBLE VIRTUAL REFERENCE STATION NETWORK AND REFERENCED TO CITY OF OCALA
 ENGINEERING DEPARTMENT CONTROL POINT 0011.
- VERTICAL DATUM BASED ON CITY OF OCALA ENGINEERING DEPARTMENT CONTROL POINT 0011WITH AN ELEVATION OF 85.20', NAVD-88.
- 7. ORIENTATION FOR THE IMPROVEMENTS SHOWN HEREON SHOULD NOT BE USED TO RECONSTRUCT BOUNDARY LINES.
- 8. ADDITIONS OR DELETIONS TO SURVEY MAPS BY OTHER THAN THE SIGNING PARTY OR PARTIES IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE SIGNING PARTY OR PARTIES.
- 9. THIS SURVEY DEPICTS THE PROPERTY AS IT EXISTED ON THE SURVEY DATE, NOT NECESSARILY THE SIGNATURE DATE.
- 10. THIS SURVEY HAS BEEN PREPARED FOR THE EXCLUSIVE BENEFIT OF THE PARTY(IES) NAMED HEREON, AND SHALL NOT BE DUPLICATED OR RELIED UPON BY ANY OTHER INDIVIDUAL OR ENTITY WITHOUT AUTHORIZATION FROM R.M. BARRINEAU & ASSOCIATES. INC.

BURIED UTILITIES

- 36. PRIOR TO DIGGING ANY TRENCHES, THE CONTRACTOR SHALL NOTIFY ALL UTILITIES (ELECTRIC, GAS, TELEPHONE, WATER, SEWER) AND OBTAIN LOCATIONS OF UNDERGROUND UTILITIES.
- 37. CONTRACTOR SHALL BE RESPONSIBLE FOR THE LOCATION AND IDENTIFICATION OF ALL EXISTING UTILITIES AND UNDERGROUND PIPELINES IN CONSTRUCTION AREA. ANY DAMAGES TO EXISTING UTILITIES OR UNDERGROUND PIPELINES ON OR OFF AIRPORT PROPERTY SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. ALL REPAIR WORK SHALL MEET THE APPROVAL OF THE OWNER OF THE DAMAGED UTILITY. NO REIMBURSEMENT WILL BE ALLOWED FOR UTILITY/PIPE REPAIR OR REPLACEMENT.
- 38. THE CONTRACTOR SHALL PROTECT EXISTING UTILITIES, AIRFIELD LIGHTING AND NAVAIDS NOT CALLED OUT TO BE REMOVED OR ABANDONED. ANY DAMAGES DONE TO AIRPORT PROPERTY OR UTILITIES (INCLUDING, BUT NOT LIMITED TO RUNWAYS, TAXIWAYS, APRONS, FENCING, EXISTING CABLES, LIGHTING, SIGNS, NAVAIDS) WILL BE REPAIRED BY THE CONTRACTOR TO THE APPROVAL OF THE OWNER OF THE FACILITY IN A SATISFACTORY MANNER. THE CONTRACTOR WILL BEAR ALL COSTS FOR REPAIRS.
- 39. ANY UNPLANNED, UNAPPROVED, OR ACCIDENTAL SHUTDOWN OR INTERRUPTION OF SERVICE TO ANY LIGHTING CIRCUIT OR NAVIGATIONAL AID REQUIRES IMMEDIATE NOTIFICATION OF AIRPORT OPERATIONS AND THE OWNER'S REPRESENTATIVE BY THE CONTRACTOR. THE COST OF MATERIALS AND LABOR REQUIRED TO REPAIR THE LIGHTING CIRCUIT SHALL BE BORNE BY THE CONTRACTOR.







Project Nar

NORTH DEVELOPMENT ROAD

Designer:	Checked By:							
MA	TL							
Technician:	ICE Project Name:							
AM	23-024							

Engineer of Record:



-	
- 1	NOTES:

REVISIONS							
NO.	DESCRIPTION	DATE	BY				
_							
	g Name:						

GENERAL NOTES

FAA A.I.P. Project No.:

FDOT Project No.:

449858-94-01

Date: Sheet Number

MARCH 2024

G2.1

C:Users/AMR,MANSOUR/Box/ICETPAAV/AT/ON/Ocala/23-024 North Development Road/CADD-dwol(004) G2.1-(GENERAL NOTES) dwg Dale: 3/22/2024

il in	Lake City, FL 32024 Telephone: 386-755-3633 Fax: 386-755-3633							PAGE 1 OF
	Infrastructure Consulting & Engineering	P	ROJEC	T NA	ME	Oca	la Int'l Airpor	t-Northwest Access Road
	ECT NUMBER 23-00114-01						Ocala, Flori	
	STARTED 3/30/23 COMPLETED 3/30/23							HOLE SIZE 2-in dia. x 10 ft. dep
	.ING CONTRACTOR Cal-Tech Testing, IncING METHOD SPT	G	ROUNI					
	EED BY B.S. CHECKED BY I.M.						LING	
	S Elev. refered to ground surface					LLING		at encountered
1			T				DATA	5.84
ELEV.	MATERIAL DESCRIPTION	SYMBOL	DEPTH SCALE (ft)	NUMBER	TYPE	RECOVERY (%) (RQD) %	BLOW COUNTS (N VALUE)	REMARKS (DRILLING FLUID, DEPTH OF CASING, FLUID LOSS, DRILLING RESISTANCE, ETC.)
-	(SP) Yellowish brown SAND		2	1	ss	67	1-5-5-5 (10)	Boring Location Coordinates: N29°11'05.7" W82°13'54.0" SS=Split Spoon sampler
	(SP) Reddish yellow SAND		4	2	ss	67	3-3-2-4 (5)	
-5			6_	3	ss	67	1-1-2-2 (3)	
-			8_	4	ss	71	1-1-2-1 (3)	
10	(SM) Reddish yellow SILTY SAND		10	5	SS	63	1-1-2-5 (3)	
,,,,	Bottom of borehole at 10.0 feet.	1 7						

- A - A - A - A - A - A - A - A - A - A	Cal-Tech Testing, Inc. 3309 SR 247 Lake City, FL 32024 Telephone: 386-755-3633							BORING NUMBER B
CLIEN PROJE DATE	Fax: 386-755-3633	9					L 1 40 **	
	T Infrastructure Consulting & Engineering ECT NUMBER 23-00114-01							rt-Northwest Access Road
4	STARTED 3/30/23 COMPLETED 3/30/23						Ocala, Flor	HOLE SIZE _2-in dia. x 10 ft. de
1	ING CONTRACTOR Cal-Tech Testing, Inc.							
	NG METHOD SPT						LING	
1	ED BY B.S. CHECKED BY I.M.						2000 CONTRACT (2000)	ot encountered
I	Elev. refered to ground surface						;	
LOGG NOTES (#)			l		SAI	MPLE	DATA	
ELEV. (ft)	MATERIAL DESCRIPTION	SYMBOL	DEPTH SCALE	NUMBER	TYPE	RECOVERY (%) (RQD) %	BLOW COUNTS (N VALUE)	REMARKS (DRILLING FLUID, DEPTH OF CASING, FLUID LOSS, DRILLING RESISTANCE, ETC.
-	(SP) Reddish brown SAND		2	1	ss	63	1-2-2-2 (4)	Boring Location Coordinates: N29°10'57.3" W82°13'54.2" SS=Split Spoon sampler
-	(SP) Yellowish red DSAND		4	2	ss	67	1-1-1-1 (2)	
-5	(SM) Gray and yellowish red SILTY SAND		6_	3	SS	63	1-3-5-9 (8)	
-			8_	4	ss	67	12-12-18- 16 (30)	
-10			10	5	ss	71	20-22-22- 21 (44)	







NORTH DEVELOPMENT ROAD

Designer:	Checked By:
MA	ŤL
Technician:	ICE Project Name
AM	23-024

Engineer of Record:



	REVISIONS						
NO.	DESCRIPTION	DATE	BY				
Drav	ving Name:						
	GENERAL NOTES						
FAA	A.I.P. Project No.:						

FDOT Project No.:

449858-94-01 Sheet Number:

MARCH 2024

G2.1

C	Cal-Tech Testing, Inc. 3309 SR 247 Lake City, FL 32024 Telephone: 386-755-3633 Fax: 386-755-3633							BORING NUMBER B3 PAGE 1 OF 1
	Infrastructure Consulting & Engineering	F	ROJEC	T NA	ME	Oca	la Int'l Airpo	rt-Northwest Access Road
	NUMBER 23-00114-01		ROJEC	T LO	CAT	TION	Ocala, Flor	ida
	ARTED 3/30/23 COMPLETED 3/30/2							HOLE SIZE 2-in dia. x 10 ft. dept
	CONTRACTOR Cal-Tech Testing, Inc.		ROUN					
	METHOD SPT						LLING	
	BY B.S. CHECKED BY I.M. Elev. refered to ground surface							ot encountered
NOIES .	Elev. resered to ground surrace		_	IER			E	T
			H.		SA		DATA	
ELEV.	MATERIAL DESCRIPTION	SYMBOL	DEPTH SCALE (ft)	NUMBER	TYPE	RECOVERY (%) (RQD) %	BLOW COUNTS (N VALUE)	REMARKS (DRILLING FLUID, DEPTH OF CASING, FLUID LOSS, DRILLING RESISTANCE, ETC.)
-	(SP) Yellowish red SAND		2_	1	SS	58	1-1-2-2	Boring Location Coordinates: N29*10'58.5" W82*13'45.1" SS=Split Spoon sampler
			4_	2	ss	67	1-2-1-1 (3)	
-5			6_	3	ss	71	1-1-1-2 (2)	
			8_	4	ss	75	1-2-1-1 (3)	
-10			 10	5	SS	75	1-2-2-2 (4)	
	Bottom of borehole at 10.0 feet.							

To the second	Lake City, FL 32024 Telephone: 386-755-3633 Fax: 386-755-3633							PAGE 1 OF
	Infrastructure Consulting & Engineering	F	ROJEC	T NA	ME	Oca	la Int'l Airpor	rt-Northwest Access Road
		F						3. 40. 40.
	STARTED 3/30/23 COMPLETED 3/30/23							HOLE SIZE 2-in dia. x 5 ft. dept
	NG CONTRACTOR Cal-Tech Testing, Inc.		ROUN	WA1	TER	LEVI	ELS:	
	NG METHOD SPT							
	ED BY B.S. CHECKED BY I.M.							ot encountered
NOTES	Elev. refered to ground surface		AF				<u> </u>	
			쁘		SAI		DATA	
ELEV.	MATERIAL DESCRIPTION	SYMBOL	DEPTH SCALE	NUMBER	TYPE	RECOVERY (%) (RQD) %	BLOW COUNTS (N VALUE)	REMARKS (DRILLING FLUID, DEPTH OF CASING, FLUID LOSS, DRILLING RESISTANCE, ETC.)
	(SP) Yellowish red SAND			1	ss	58	1-1-2-5 (3)	Boring Location Coordinates: N29°10'59.9" W82°13'43.6" SS=Split Spoon sampler
-			4	2	ss	67	4-3-3-3 (6)	
-5			F -	3	ss	83	1-1	
-5	Bottom of borehole at 5.0 feet.				+			





INFRASTRUCTURE CONSULTING & ENGINEERING 5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 3364, (813) 330-2701 CERTIFICATE OF AUTHORIZATION NO.: 30862

NORTH DEVELOPMENT ROAD

Designer:	Checked By:				
MA	TL				
Technician:	ICE Project Name				
AM	23-024				

Engineer of Record:



REVISIONS								
١٥.	DESCRIPTION	DATE	BY					
	- 27							
	ALL LINE							
rawing	Name:							
	GENERAL N	NOTES						

FAA A.I.P. Project No.:

FDOT Project No.:

449858-94-01 Sheet Number:

MARCH 2024

G2.1

	Cal-Tech Testing, Inc. 3309 SR 247 Lake City, FL 32024 Telephone: 386-755-3633 Fax: 386-755-3633							BORING NUMBER PAGE 1
CLIEN	Infrastructure Consulting & Engineering		PROJEC	T NA	ME	Oca	la Int'l Airpo	rt-Northwest Access Road
PROJE	ECT NUMBER 23-00114-01		ROJE	T LO	CAT	ION	Ocala, Flor	rida
DATE	STARTED 3/30/23 COMPLETED 3/30/23	(ROUN	D ELE	VA	TION	0 ft	HOLE SIZE 2-in dia. x 5 ft. o
DRILLI	NG CONTRACTOR Cal-Tech Testing, Inc.	(ROUN	D WA	TER	LEV	ELS:	
DRILLI	NG METHOD SPT		A1	TIME	OF	DRIL	LING	
LOGGE	ED BY B.S. CHECKED BY I.M.		A	END	OF	DRIL	LING N	ot encountered
NOTES	Elev. refered to ground surface		AF	TER	DRI	LLING	<u> </u>	
	324		l	I	SAI	MPLE	DATA	
ELEV.	MATERIAL DESCRIPTION	SYMBOL	DEPTH SCALE (ft)	NUMBER	TYPE	RECOVERY (%) (RQD) %	BLOW COUNTS (N VALUE)	REMARKS (DRILLING FLUID, DEPTH OF CASIN- FLUID LOSS, DRILLING RESISTANCE, E
	(SP) Reddish brown SAND			1	ss	58	1-1-3-2 (4)	Boring Location Coordinates: N29°10'59.1" W82°13'47.5" SS=Split Spoon sampler
+	(SP) Reddish yellow SAND		_ 2 _	2	ss	63	1-2-1-2	
-			_ 4 _	3	ss	50	1-1	

il.	Lake City, FL 32024 Telephone: 386-755-3633 Fax: 386-755-3633							
CLIEN	T Infrastructure Consulting & Engineering	P	ROJEC	T NA	ME	Oca	la Int'l Airpor	t-Northwest Access Road
	PROJECT NUMBER 23-00114-01 DATE STARTED 3/30/23 COMPLETED 3/30/23 DRILLING CONTRACTOR Cal-Tech Testing, Inc.						Ocala, Flori	
DATE				ELE	VA	TION	0 ft	HOLE SIZE 2-in dia. x 5 ft. dept
DRILLI				WAT	TER	LEVI	ELS:	
	NG METHOD SPT		AT	TIME	OF	DRIL	LING	
	ED BY B.S. CHECKED BY I.M.		AT	END	OF	DRIL	LING No	ot encountered
NOTES	Elev. refered to ground surface		AF	TER	DRI	LLING	3	
			Щ		SAI	MPLE	DATA	
ELEV.	MATERIAL DESCRIPTION	SYMBOL	DEPTH SCALE (ft)	NUMBER	TYPE	RECOVERY (%)	BLOW COUNTS (N VALUE)	REMARKS (DRILLING FLUID, DEPTH OF CASING, FLUID LOSS, DRILLING RESISTANCE, ETC.)
	(SP) Yellowish red SAND		2	1	ss	63	1-2-4-3 (6)	Boring Location Coordinates: N29°10'59.0" W82°13'49.5" SS=Split Spoon sampler
			 - 4 _	2	ss	67	2-2-2-2 (4)	
-5				3	ss	83	1-1	







NORTH DEVELOPMENT ROAD

Designer:	Checked By:				
MA	TL				
Technician:	ICE Project Name:				
AM	23-024				

Engineer of Record:



IOTES:	

REVISIONS							
NO.	DESCRIPTION	DATE	BY				
-							
	· ·						
Drawin	g Name:						
	GENERAL N	NOTES					
FAA A	I P Project No:						

A.I.P. Project No.:

FDOT Project No.:

449858-94-01 e: Sheet Number:

MARCH 2024

G2.1

CUENT IN	Cal-Tech Testing, Inc. 3309 SR 247 Lake City, FL 32024 Telephone: 386-755-3633 Fax: 386-755-3633 rastructure Consulting & Engineering		PO IEC	T NAI	ME	Ocal	a Int'l Airne	BORING NUMBER I
	UMBER 23-00114-01						Ocala, Flor	rt-Northwest Access Road
	TED <u>3/30/23</u> COMPLETED <u>3/30/23</u>							HOLE SIZE 2-in dia. x 5 ft. de
	ONTRACTOR Cal-Tech Testing, Inc.		ROUNE					HULE SIZE Z-III GIZ. X 3 IL, GI
	ETHOD SPT							
	B.S. CHECKED BY I.M.						LING	
	v. refered to ground surface						300000000000000000000000000000000000000	ot encountered
NOTES Elec	v. refered to ground surface		AF					
			E E		SAI		DATA	
ELEV.	MATERIAL DESCRIPTION	SYMBOL	DEPTH SCALE	NUMBER	TYPE	RECOVERY (%)	BLOW COUNTS (N VALUE)	REMARKS (DRILLING FLUID, DEPTH OF CASING FLUID LOSS, DRILLING RESISTANCE, ET
_ (SF	P) Yellowish red SAND		2_	1	ss	42	1-1-1-1 (2)	Boring Location Coordinates: N29*11'0.2" W82*13'51.4" SS=Split Spoon sampler
			4_	2	ss	63	1-1-1-1 (2)	
-5			+ +	3	ss	92	1-1	

Cal-Tech Testing, Inc. 3309 SR 247 Lake City, FL 32024 Telephone: 386-755-3633 Fax: 386-755-3633							BORING NUMBER B
CLIENT Infrastructure Consulting & Engineering	PI	ROJEC	T NA	ME	Oca	la Int'l Airpoi	t-Northwest Access Road
PROJECT NUMBER _23-00114-01	PI	ROJEC	T LO	CAT	ION	Ocala, Flori	da
DATE STARTED 3/30/23 COMPLETED 3/30/23	G	ROUNI	D ELE	VAT	rion	0 ft	HOLE SIZE 2-in dia. x 5 ft. dept
ORILLING CONTRACTOR Cal-Tech Testing, Inc.	G	ROUNI	D WA	TER	LEVI	ELS:	
PRILLING METHOD SPT						LING	
OGGED BY B.S. CHECKED BY I.M. IOTES Elev. refered to ground surface							ot encountered
Elev. refered to ground surface		_				DATA	
MATERIAL DESCRIPTION	SYMBOL	DEPTH SCALE (ft)	NUMBER	TYPE	RECOVERY (%)	BLOW COUNTS (N VALUE)	REMARKS (DRILLING FLUID, DEPTH OF CASING, FLUID LOSS, DRILLING RESISTANCE, ETC.)
(SP) Yellowish red SAND			1	ss	67	1-3-3-4 (6)	Boring Location Coordinates: N29*117.7" W82*13'53.9" SS=Split Spoon sampler
		_ 4 _	2	ss	71	2-2-1-2 (3)	
-5			3	SS	58	1-1	







NORTH DEVELOPMENT ROAD

Designer: Checked By: TL
Technician: ICE Project Name: AM 23-024

Engineer of Record:



NOTES

REVISIONS									
10.	DESCRIPTION	DATE	BY						
rawing	Name:								
	GENERAL N	OTES							

FAA A.I.P. Project No.:


FDOT Project No.:

449858-94-01

MARCH 2024

G2.1

paragrams Mansoli BismalcETPAAAJATIONIOnala/2-024 Morth Develorment BraditCADD-dwyl/0041 G3 1-63 5- BOBING I OGS dwn Date: 3/2/2









NORTH DEVELOPMENT ROAD

Designer: MA	Checked By: TL
Technician:	ICE Project Name:
AM	23-024

Engineer of Record:



•	_					
1	N	Λ	Т	F	ς	

REVISIONS							
NO.	DESCRIPTION	DATE	BY				
_							
-							

GENERAL NOTES

FAA A.I.P. Project No.:


FDOT Project No.:


449858-94-01


MARCH 2024


G2.1


MANSOURBoxilCETPAAVATION!Ocalai/23-024 North Development Road/CADD-dwa\(1004\) G3 1-G3-5-BORING LOGS dwa Date: 3/22/202






































Designer:	Checked By:		
MA	TL		
Technician:	ICE Project Name:		
AM	23-024		



F	EVISIONS	

DATE BY

Drav	ving Name: STAKING AND GE PLANS (4 OI	OMETR F 5)	Υ
_			


C3.4

Project Name: NORTH DEVELOPMENT ROAD 3 3 TYP. PAVED SHLDR PC: 10+25 79 PROPOSED ACCESS ROAD Engineer of Record: DESCRIPTION 6' CHAIN LINK FENCE EXISTING RECLAIM WATER SYSTEM FAA A.I.P. Project No.: DOT Project No.: 449858-94-01 MARCH 2024

MATCH LINE SHEET C3.2

C3

O









NORTH DEVELOPMENT ROAD

CE Project Name: 23-024



REVISIO	NS			
ESCRIPTION DATE				

Drav	ving Name:	

STAKING AND GEOMETRY PLANS (5 OF 5)


FAA A.I.P. Project No.:


FDOT Project No.:


449858-94-01


MARCH 2024


C3.5

















NORTH DEVELOPMENT ROAD

ICE Project Name: 23-024

Engineer of Record:



1. SEE SHEET C4.1 FOR LEGEND

NO.	DESCRIPTION	DATE	BY
+			
-			
		+	
+		+	
+			
\dashv			
_			

REVISIONS

GRADING AND DRAINAGE PLANS (5 OF 5)


FAA A.I.P. Project No.:


FDOT Project No.:


449858-94-01

MARCH 2024 C4.5

MATCH LINE SHEET C4.3 BEGIN TREATMENT DITCH / STA: 19+13.38 EL: 79.38 - ACCESS ROAD END STA 19+13.38 - CONTRACTOR TO GRADE 20'X20' , AREA NEW ACCESS ROAD











NORTH DEVELOPMENT ROAD

Designe necked By AM 23-024

Engineer of Record:



REVISIONS DESCRIPTION DATE

CONSTRUCTION DETAILS (1 OF 4)

FAA A.I.P. Project No.

FDOT Project No.:


449858-94-01

Sheet Number:

MARCH 2024

C4.6

25 FT WIDE









Project Name:

NORTH DEVELOPMENT **ROAD**

E Project Name: 23-024 AM

Engineer of Record:



REVISIONS						
NO.	DESCRIPTION	DATE	BY			
-		-				
-						
-		-				
-		_				
Drawin	CONSTRUC					

DETAILS (2 OF 4)


FDOT Project No.:


449858-94-01

MARCH 2024

C4.7

Sheet Number:











NORTH DEVELOPMENT ROAD

Designer: Checked By:

MA TL

Technician: ICE Project Name:

AM 23-024

Engineer of Reco



REVISIONS

Drawing Name:


CONSTRUCTION
DETAILS (3 OF 4)

FAA A.I.P. Project No.:

-
FDOT Project No.:

C4.8

MARCH 2024



Ocala International Airport





Project Nam

NORTH DEVELOPMENT ROAD

Designer: Checked By: TL

Technician: ICE Project Name: AM 23-024

Engineer of Record:



NOTES

	REVISIO	NS	
NO.	DESCRIPTION	DATE	BY
-		-	
		-	
		<u> </u>	
		-	
Drawin	Name:		
Drawin	CONSTRUC	CTION	
l	DETAILS (A	OF A)	

DETAILS (4 OF 4)


FAA A.I.P. Project No.:

FDOT Project No.:

449858-94-01


449858-94-0


MARCH 2024 Sheet Number:




CONCRETE PIPE CONNECTOR DETAIL FOR MITERED END SECTION

	DIMENSIONS													
												М		
	D	X	Α	В	С	E	F	G	Н 🔳	Single	Double	Triple	Quad.	N
					NTS					Pipe	Pipe	Pipe	Pipe	
1:4	15"	2'-7"	2.27'	4.09'	6.36'	4.03'	8'	1.22'	4.0'	4.63'	7.21'	9.79'	12.37'	1.19'
Slope	18"	2'-10"	2.36'	5.12'	7.48'	5.03'	9'	1.41'	4.0'	4.92'	7.75'	10.58'	13.42	1.21'
Stope	24"	3'-5"	2.53'	7.18' △	9.71'	7.03' △	11'	1.73'	4.0'	5.50'	8.92'	12.33'	15.75'	1.25'







MITERED END SECTION (M.E.S.) FOR SINGLE ROUND CONCRETE PIPE



Pond 1RT Overflow Weir











Project Name:

NORTH DEVELOPMENT ROAD


Engineer of Record:



NOTES

	REVISIONS							
NO.	DESCRIPTION		DATE	BY				
_								
			-					
Drav	wing Name:							
	DRAINAGI	E DE	ETAILS					
FΔΔ	A.I.P. Project No.:							
1200	Talli : Troject No.:							
FDOT Project No.:								
	449858-94-01							
Date	8:	Sheet	Number:					
M	MARCH 2024 C4.10							









NORTH DEVELOPMENT **ROAD**

necked By MA AM 23-024

Engineer of Record:



REVISIONS DESCRIPTION DATE

_	

DRAINAGE DETAILS


FAA A.I.P. Project No.:


FDOT Project No.:

449858-94-01

Sheet Number: MARCH 2024

C4.11












NORTH DEVELOPMENT ROAD

Designer:	Checked By:	
MA	TL	
Technician:	ICE Project Name	
AM	23-024	





REVISIONS				
DESCRIPTION	DATE	BY		
ring Name:				
PLAN & PROFILE	(2 OF 2)		
	DESCRIPTION	DESCRIPTION DATE		


FDOT Project No.:


449858-94-01


Sheet Number:


MARCH 2024

C5.2















NORTH DEVELOPMENT ROAD

Checked By: CE Project Name: 23-024

Engineer of Record:




REVISIONS				
NO.	DESCRIPTION	DATE	BY	
			1	
			-	
_			├	
-			-	
Drawing	Name:			
_	DOSS SECTION	IC /4 OF	14)	
	ROSS SECTION	13 (1 OF	11)	
FAA A.I	.P. Project No.:			


449858-94-01

MARCH 2024

FDOT Project No.:

C6.1












NORTH DEVELOPMENT ROAD

MA CE Project Name: 23-024

Engineer of Record:






REVISIONS							
NO.	DESCRIPTION	DATE	BY				
-		-					
-		+					
Drawie	a Nama						
	g Name: ROSS SECTION	IS (2 OF 1	11)				


FAA A.I.P. Project No.: FDOT Project No.:

449858-94-01 Sheet Number:

MARCH 2024

C6.2











NORTH DEVELOPMENT **ROAD**

Designer: MA	Checked By: TL
Technician:	ICE Project Name:
AM	23-024



REVISIONS						
NO.	DESCRIPTION	DATE	B			
-		-	_			
		+	-			
		-				
	-	_				


FAA A.I.P. Project No.:


FDOT Project No.:

449858-94-01

MARCH 2024

C6.3











NORTH DEVELOPMENT ROAD

MA

Engineer of Record:



	VERT. SCALE					
REVISIONS						
NO.	DESCRIPTION	DATE	BY			
		-				
-		+				
	N					
Drawin	g Name:					
С	ROSS SECTION	IS (4 OF 1	11)			


FDOT Project No.:


449858-94-01


MARCH 2024


C6.4

Sheet Number:















NORTH DEVELOPMENT ROAD

Checked By: MA CE Project Name: 23-024

Engineer of Record:



NO.	05000000000	D. T.	-
NO.	DESCRIPTION	DATE	BY
		-	-
_		_	_
_		-	
_		-	
Drowing	g Name:		
	9 1101110.		


FAA A.I.P. Project No.:


FDOT Project No.:


449858-94-01


Sheet Number: MARCH 2024

C6.5















NORTH DEVELOPMENT ROAD

Designer:

MA

TL

Technician:

AM

Checked By:

TL

TL

Technician:

ICE Project Name:


AM

23-024

Engineer of Record:



NOTES:



REVISIONS
DESCRIPTION DA

Drav	ving	Name	:			

CROSS SECTIONS (6 OF 11)

FAA A.I.P. Project No.:


FDOT Project No.:


449858-94-01


MARCH 2024


Sheet Number: C6.6

C.N. sersiaMR MANSOLIPRIBOXICETPANAVIATION/Ocala/23-024 North Development Road/CADD-dwolf012) C6 1-C6 10-CROSS













NORTH DEVELOPMENT ROAD

Designer: Checked By:

MA TL

Technician: ICE Project Name:

AM 23-024

Engineer of Record:



0 10 20 40
HORIZ, SCALE
0 2.5 5 10
VERT. SCALE

REVISIONS						
NO.	DESCRIPTION	DATE	BY			
			-			
	(A)	-				
-		_				
	**					
Drawing	Name:					
CROSS SECTIONS (7 OF 11)						
FAA AI	P Project No :					


...


FDOT Project No.: 449858-94-01


Date: Sheet


MARCH 2024

C6.7













NORTH DEVELOPMENT ROAD

Checked By:

Engineer of Record:



NO.	DESCRIPTION	DATE	DV
NO.	DESCRIPTION	DATE	BY
_			
-			-
_		_	_
Drawin	g Name:		


FAA A.I.P. Project No.:


FDOT Project No.:


449858-94-01


MARCH 2024

C6.8















NORTH DEVELOPMENT ROAD

Designer:

MA

TL

Technician:

AM

Checked By:

TL

TL


Technician:

ICE Project Name:
23-024

Engineer of Recor



NOTES:



REVISIONS

DESCRIPTION DATE BY

CROSS SECTIONS (9 OF 11)

FAA A.I.P. Project No.:


FDOT Project No.: 449858-94-01


Date: |Sk


MARCH 2024


C6.9

VICETEANAVIATIONIO asia 123-024 North Development Board CADD-dwolf (13) C6 1-C6 10-CBOSS SECTIONS dwa Date: 3/22/21















Project Na

NORTH DEVELOPMENT ROAD

Designer:

MA

TL

Technician:

AM


Checked By:

TL

1CE Project Name:
23-024

Engineer of Record:






	REVISIO	NS	
NO.	DESCRIPTION	DATE	BY
Drawin	g Name:		
_	0000 000	0 // 0 0=	
C	ROSS SECTION	S (10 OF	11)
FAA A.	I.P. Project No.:		


FDOT Project No.: 449858-94-01


MARCH 2024

C6.10

IIONIOralai23-024 North Development Roadif CADD-dwidf012) CR 1-08 10- CROSS SECTIONS dw












NORTH DEVELOPMENT **ROAD**

Checked By: TL ICE Project Name: 23-024

Engineer of Record:





REVISIONS DESCRIPTION Drawing Name: CROSS SECTIONS (11 OF 11)


FAA A.I.P. Project No.:

FDOT Project No.:

449858-94-01

Sheet Number: MARCH 2024

C6.11



STORMWATER POLLUTION PREVENTION PLAN

- 1. SILT FENCING AND ROCK CHECK STRUCTURES WILL BE REQUIRED TO CONTROL EROSION AS SHOWN ON THE PLANS OR AT LOCATIONS DETERMINED BY THE ENGINEER. THE CONTRACTOR SHALL IMPLEMENT AND MAINTAIN THESE MEASURES THROUGHOUT CONSTRUCTION, ALL EROSION CONTROL DEVICES SHALL BE INSTALLED PRIOR TO ANY EXCAVATION OR CLEARING AND GRUBBING WORK, THE QUANTITY OF TEMPORARY EROSION AND SEDIMENTATION CONTROL DEVICE MAY BE INCREASED OR DECREASED FROM THAT SHOWN IN THE DRAWINGS BASED ON WEATHER, CONSTRUCTION PROCEDURES AND ACTUAL SITE CONDITIONS THAT OCCUR DURING CONSTRUCTION. SUCH VARIATIONS WILL NOT BE CONSIDERED AS ALTERATIONS IN THE DETAILS OF CONSTRUCTION OR A CHANGE IN THE CHARACTER OF
- 2. SILT FENCE SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 104 OF THE FDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION. FILTER FABRIC FOR SILT FENCE AND INLET PROTECTION SHALL BE IN ACCORDANCE WITH SECTION 985 OF THE FDOT STANDARD SPECIFICATIONS.
- 3. ALL DISTURBED AREAS ARE TO BE SODDED IN ACCORDANCE WITH FDOT SPECIFICATIONS SECTION 570 WITHIN 14 DAYS OF THE COMPLETION OF GRADING OPERATIONS AND WITHIN THE PRESCRIBED PHASING
- 4. ANY FINES, PENALTIES, OR OTHER COSTS ASSESSED BY STATE, LOCAL OR OTHER GOVERNMENTAL AGENCIES FOR NON-PERFORMANCE OF THE EROSION CONTROL REQUIREMENTS OF THIS PROJECT AGAINST THE AIRPORT AUTHORITY SHALL BECOME THE RESPONSIBILITY OF THE CONTRACTOR, AND ANY SUCH ASSESSMENTS, IF NOT PAID BY THE CONTRACTOR, WILL BE DEDUCTED FROM MONIES DUE AT THE COMPLETION OF THE PROJECT.
- 5. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FILING AN NPDES NOTICE OF INTENT (NOI) TO USE GENERIC PERMIT FOR STORMWATER DISCHARGE FROM LARGE AND SMALL CONSTRUCTION ACTIVITIES FROM FDEP. THE CONTRACTOR WILL ALSO BE REQUIRED TO FILE A NOTICE OF TERMINATION (NOT) AT THE COMPLETION OF THE PROJECT. THE CONTRACTOR SHALL BE NAMED AS THE OPERATOR IN THE (NOI) AND MAY ENTER A STATEMENT ON THE FORM THAT "THERE ARE NO ATTACHMENTS SUBMITTED WITH THIS DOCUMENT" TO ADDRESS THAT THE CONTRACTOR DID PREPARE THE STORMWATER POLLUTION PROTECTION PLAN.

MAINTENANCE PLAN

- 1. ALL EROSION AND SEDIMENT CONTROL PRACTICES WILL BE CHECKED FOR STABILITY AND OPERATION FOLLOWING EVERY RUNOFF-PRODUCING RAINFALL BUT IN NO CASE LESS THAN ONCE EVERY WEEK. ANY NEEDED REPAIRS WILL BE MADE IMMEDIATELY TO MAINTAIN ALL PRACTICES AS DESIGNED.
- 2. SEDIMENT WILL BE REMOVED FROM THE INLET PROTECTION DEVICES WHEN STORAGE CAPACITY HAS BEEN APPROXIMATELY 50% FILLED OR AS DIRECTED BY THE ENGINEER. GRAVEL WILL BE CLEANED OR REPLACED WHEN SEDIMENT POOL NO LONGER DRAINS PROPERLY.
- 3. SEDIMENT WILL BE REMOVED FROM BEHIND THE TEMPORARY SILT FENCE WHEN IT BECOMES 0.5 FT. DEEP AT THE FENCE. THE TEMPORARY SILT FENCE WILL BE REPAIRED AS NECESSARY TO MAINTAIN A BARRIER. TEMPORARY DIVERSION SWALES WILL BE CHECKED AFTER EVERY RAINFALL AND ANY SIGNIFICANT SEDIMENT BUILD UP WILL BE REMOVED AS DIRECTED BY THE ENGINEER.
- 4. ANY ACCUMULATIONS OF SEDIMENT IN EXISTING STORMWATER BASINS SHALL BE REMOVED AT THE END OF THE PROJECT AND THE AREA SODDED AS DIRECTED BY THE ENGINEER.







Project Name:

NORTH DEVELOPMENT **ROAD**

Designer:	Checked By:
MA	TL
Technician:	ICE Project Name:
AM	23-024

naineer of Record:



1	_					
п	N	0	Ŧ	С	C	

REVISIONS						
NO.	DESCRIPTION	DATE	BY			
Drawin	g Name:					
	(SWPP NC	TES)				

DEVICIONO


(SWPP NOTES)

AA A.I.P. Project No.:


FDOT Project No.:

449858-94-01


heet Number: MARCH 2024 C7.2



NOTE: SIGNS INSTALLED WITHIN SIDEWALKS SHALL BE SET DIRECTLY IN THE CONCRETE AND SHALL UTILIZE A 3" DIAMETER SIGN POST PER THE SPECIFICATIONS.



SIGN BASE WITHIN LANDSCAPED AREA



SIGN BASE WITHIN PAVED AREA



STOP SIGN

N.T.S

ALL STOP SIGNS SHALL BE DIAMOND GRADE DG3 REFLECTIVE **SHEETING SERIES 4000**



OCALA

Engineer of Record:



REVISIONS


DESCRIPTION

MARKING DETAILS (10F3)

FDOT Project No.: 449858-94-01

MARCH 2024 C9.1

SIGN BASE







Ocala International Airport





Project Name:

NORTH DEVELOPMENT ROAD

AM 23-024



REVISIONS				
DESCRIPTION DATE				

		1	
		_	
		1	
_			-
- 1			
_			_
			_
1			
t			
l l		1	1
- 1			
_			
- 1			
Drawing	Name:		
	54		
	MADIZINIO DETAI	10 000	•
	MARKING DETA	ILS (ZUF)	3)


FAA A.I.P. Project No.:

449858-94-01

MARCH 2024

DOT Project No.:

C9.2









NORTH DEVELOPMENT **ROAD**

23-024




REVISIONS

Drawin	g Name:		
	MARKING DETAI	LS (30F	3)


449858-94-01

MARCH 2024

C9.3



STANDARD BRACING PANEL/ CORNER POST



STANDARD BRACING/ PULL POST PANEL

N.T.S.







Project Name:

NORTH DEVELOPMENT ROAD

Designer: Checked By:

MA TL

Technician: ICE Project Name:

AM 23-024

Engineer of Record:



NOTES

REVISIONS							
NO.	DESCRIPTION	DATE	BY				
Drawin	g Name:						
FENCE AND GATE DETAILS							

FAA A.I.P. Project No.:


FDOT Project No.:


449858-94-01

Date: Sheet Number:

MARCH 2024

C10.1






LINE POST

CORNER POST

NOTE: EXTENSION ARMS TO BE ANGLED OUTWARD AND AWAY FROM AIRFIELD SIDE OF FENCING (TYP.)

BARBED WIRE SUPPORT ARM DETAILS



TYPICAL FENCE GROUNDING DETAIL

FENCE ELECTRICAL GROUNDING NOTE:

1. ELECTRICAL GROUNDS SHALL BE CONSTRUCTED AT THE FOLLOWING LOCATIONS:

A) WHERE A POWER LINE PASSES OVER OR UNDER THE FENCE, THE GROUND SHALL BE INSTALLED DIRECTLY BELOW THE POINT OF CROSSING.

B) AT MAXIMUM 500-FOOT INTERVALS ALONG THE FENCE,

C) AT EACH GATE LEAF AND EACH GATE POST ON BOTH SIDES OF EACH GATE.

2. THE GROUND SHALL BE ACCOMPLISHED WITH A COPPER-CLAD ROD 8 FEET LONG AND A MINIMUM OF 5/8 INCH IN DIAMETER DRIVEN VERTICALLY UNTIL THE TOP IS 6 INCHES BELOW THE GROUND SURFACE. A NO. 6 SOLID COPPER CONDUCTOR SHALL BE CLAMPED TO THE ROD AND TO THE FENCE IN SUCH A MANNER THAT EACH ELEMENT OF THE FENCE IS GROUNDED.

3. INSTALLATION OF GROUND RODS SHALL NOT CONSTITUTE A PAY ITEM AND SHALL BE CONSIDERED INCIDENTAL TO THE LINE ITEM FOR FENCING.







NORTH DEVELOPMENT **ROAD**

CE Project Name 23-024



ı		
ı	MOTEC	

NO.	DECODISTION	DATE	D).
NU.	DESCRIPTION	DATE	BY
	-		
-			
-			

FENCE AND GATE DETAILS


FDOT Project No.:


449858-94-01


MARCH 2024

C10.2

Sheet Number:







Contact Information:	Manufacturer:	Part Number:	Product Description:	Product Specifications:
Web: www.TigerTeethStore.com Phone: (800) 878-7829 Email: Sales@TigerTeethStore.com	Barrier Gate Brands™	14010-12	SENTINEL 14ft. Manual Swing Barrier Gate	 Width: 14ft. Material: Galvanized Steel Installation Type: In-Ground Barrier Gate Type: Manual Single Swing Gate









NORTH DEVELOPMENT **ROAD**

Project Name: 23-024

Ingineer of Record:



_		_		_			
		F١	/1	CI	0	N	C
	_	г١	/ 1	ור		1	

DATE

DESCRIPTION


Drav	ving Name:		
	FENCE AND GATE	DETAIL	_S
EAA	ALD Brainst No.		


FDOT Project No.:

449858-94-01

MARCH 2024

C10.4








NOTE

SEE KEYNOTES, SHEET UP-05

HORIZONTAL

GRAPHIC SCALE (FT)



INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 ERTIFICATE OF AUTHORIZATION NO.: 308



AVCON, INC.

AVCOIN, INC.


ENGINEERS & PLANNERS

5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL. 32822-2779

OFFICE: (407) 599-1122 - FAX: (407) 599-1133

CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

NORTH DEVELOPMENT ROAD





Digitally signed by Robert H *= Palm Date: 2024.03.18 14:45:44 -04'00'

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

PROFESSIONAL SEAL


REVISIONS


			-,
_	-	+-	1
-			+-
			1
\rightarrow		+	+
\rightarrow			_
-			+
\rightarrow		+	+
Drawing	Name: UTILITY P	IAN	
	AND PRO		
	(SHEET 1 (OF 3)	
FAA	A.I.P. Project No.:	-	
	•		

FDOT Project No.: XXXXX

heet Number


FEBRUARY 2024 **UP-01**






projectslori_airports_0607091Projects\2023\2023.262.01 - ocf north dev road utilities\2023.262.01 - cadd\2326201001UP01.dwg Dat

Date: Sheet Number: FEBRUARY 2024 UP-02





NOTE

SEE KEYNOTES, SHEET UP-05



INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 ERTIFICATE OF AUTHORIZATION NO.: 3086



AVCON, INC.
ENGINEERS & PLANNERS
5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL 32822-2779
OFFICE: (407) 99-11-23
CORPORATE CERTIFICATE OF AUTHORIZATION HUMBER: 5957

NORTH DEVELOPMENT **ROAD**

	Designer: RP	Checked by: RP
0	Technician: JP	ICE Proj. No.: 23-024

Engineer of Record:



Digitally signed by Robert H Palm 2024.02.21

-05'00' ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

REVISIONS

).	Description	Date	Ву
			Т
1		1	
1	-		\top
		\neg	
awing Name	UTILITY F	PLAN	

AND PROFILE (SHEET 3 OF 3)

FAA A.I.P. Project No.:


XXXXXXX


FDOT Project No.:


XXXXX

UP-03 FEBRUARY 2024

84.0 2" BLOWOFF - ASSEMBLY WITH METER BOX 82.0 PROPOSED SURFACE 82.0 80.0 EXISTING SURFACE 78.0 76.0 74.0 72.0 72.0 - END OF WATER MAIN-70.0 70.0 76 LF 8" PVC SAN @ 0.40% 254 LF 8" PVC SAN @ 0.40% 66.0 CLEANOUT NOT SHOWN FOR CLARITY -64.0 64.0 EXISTING ELEVATION 62.0 PROPOSED ELEVATION 60.0







NOTE

SEE KEYNOTES, SHEET UP-05



INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115
TAMPA, FLORIDA 33634 (813) 330-2701



AVCON, INC.

ENGINEERS & PLANNERS
5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL. 32822-2779
OFFICE: (407) 599-1133
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

Project Name:

NORTH DEVELOPMENT ROAD

Engineer of Record:



Digitally signed by Robert H Palm Date: 2024.02.21

The form has been digitally signed and seried by Robert II. Parts PE on the case adjusced to the seals Provided conserved for the discovered to the seals Provided conserved the seals and Provided Conserved to the seal Provided Conserved to the seals and the seals and the seals adjusced to the seals adjusc

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

FI

REVISIONS

Description

FORCE MAIN PLAN AND

PLAN AND PROFILE

FAA A.I.P. Project No.:

XXXXXX


FDOT Project No.:

XXXXX

Oate: Sheet Number: UP-04

Januariantelod simode 0607001 avraintel 2002/2022 252 01 - orf mody day mad Hilline 12022 252 01

82.0 80.0 80.0 EXISTING SURFACE 78.0 78.0 76.0 76.0 72.0 45 DEG BEND 70.0 70.0 45 DEG BEND ~ 68.0 66.0 62.0 EXISTING ELEVATION 60.0 60.0 31+00 32+00



UTILITY KEY NOTES - POTABLE WATER MAIN

- CONNECT TO EXISTING 12-INCH WATER MAIN WITH 12-INCH TAPPING SLEEVE AND TAPPING VALVE WITH VALVE BOX.
- 2 INSTALL 100 LF 12-INCH DIP WATER MAIN ALL RESTRAINED JOINTS UNDER PAVEMENT IN 30-INCH ADS HP PP CASING WITH CASCADE CASING SPACERS AT 10' MAX SPACING.
- (3) 12-INCH DUCTILE IRON FITTING WITH ALL RESTRAINED JOINTS.
- (4) 12-INCH PVC PIPE, TYP. WITH LESS THAN 4-DEGREE JOINT DEFLECTION.
- (5) 12-INCH BUTTERFLY VALVE WITH BOX.
- TERMINATE WATER MAIN WITH 12-INCH TAPPED PLUG AND 2-INCH MANUAL BLOW-OFF WITH METER
- (7) 12-INCH X 6-INCH TEE, 6-INCH GATE VALVE AND VALVE BOX, FIRE HYDRANT ASSEMBLY.

UTILITY KEY NOTES - SANITARY GRAVITY SEWER

- (10) SANITARY SEWER MANHOLE.
- $\langle 11 \rangle$ 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%.
- 2 STUB-OUT AND PLUG 8-INCH PVC WITH CLEANOUT.
- (13) LIFT STATION SITE (FINAL TBD).

UTILITY KEY NOTES - SANITARY FORCE MAIN

- (20) 4-INCH PVC SANITARY FORCE MAIN.
- (21) 4-INCH SANITARY FORCE MAIN OFFSETTING 45-DEGREE BENDS ALL RESTRAINED JOINTS.
- 2 4-INCH PLUG VALVE WITH VALVE BOX.

UTILITY KEY NOTES - OVERHEAD ELECTRIC

3-PHASE OVERHEAD ELECTRICAL POWER LINES ON POWER/LIGHT POLES AT 150-FOOT MAXIMUM SPACING.

NOTES

- 1. THE CONTRACTOR SHALL COORDINATE WITH OCALA ELECTRIC TO FURNISH AND CONSTRUCT 3-PHASE ELECTRIC POWER INFRASTRUCTURE AND LED LIGHTING IN THE ROAD CORRIDOR, INCLUDING FURNISHING SURVEY AND STAKING FOR ALL ELEMENTS REQUIRED. (OCALA ELECTRIC 352-401-6922).
- 2. THE CONTRACTOR SHALL FURNISH AND CONSTRUCT ELECTRIC POWER INFRASTRUCTURE AND SERVICE FOR THE LIFT STATION SITE. (SEE DRAWINGS EL-01 AND EL-02).
- 3. THE CONTRACTOR SHALL FURNISH AND CONSTRUCT ALL REQUIRED CIVIL, ELECTRICAL, MECHANICAL AND PLUMBING REQUIRED FOR THE PROJECT UTILITIES. (REFERENCE THESE DRAWINGS AND THE TECHNICAL SPECIFICATIONS.)
- 4. PAY ITEM NOTES THE PAY ITEMS LISTED ON THE BID FORM ARE INCLUSIVE OF ALL MATERIAL, LABOR, EQUIPMENT, TESTING, INSPECTIONS, ETC. NECESSARY FOR A COMPLETE CONSTRUCTION. PAY ITEMS FOR PIPE, PER LINEAR FOOT, ARE INCLUSIVE OF ALL FITTINGS, JOINT RESTRAINTS, APPURTENANCES, LININGS, COATINGS, DETECTIBLE MARKING TAPE, TRACEABLE WIRING, LOCATOR BALLS, TRENCHING, BEDDING, BACKFILL, COMPACTION, AND ALL OTHER INCIDENTALS NECESSARY FOR A COMPLETE UTILITY CONSTRUCTION. NO SEPARATE PAYMENT WILL BE MADE FOR ITEMS FOR WHICH NO SPECIFIC PAY ITEM IS IDENTIFIED ON THE BID DOCUMENTS. THE CONTRACTOR SHALL INCLUDE SUFFICIENT BID PRICES AT THE TIME OF THE BID TO COVER THE COST OF ALL SUCH NECESSARY INCIDENTALS RESULTING IN A COMPLETE CONSTRUCTION IN ACCORDANCE WITH THE PLANS AND TECHNICAL SPECIFICATIONS.

UTILITY KEY NOTES

- (11A) 60 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-11) 69 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-1) 194 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-2) 108 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-2A) 30 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-3) 94 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-10) 48 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.54%
- (P-8) 390 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-7) 98 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-6) 187 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-6A) 30 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-6B) 30 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-5) 254 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-5A) 30 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-5B) 30 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-4) 254 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-4A) 30 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-4B) 76 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL
- (P-4C) 30 LF 8-INCH PVC SANITARY GRAVITY SEWER AT 0.40%, TYPICAL



INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115
TAMPA, FLORIDA 33634 (813) 330-2701
CERTIFICATE OF AUTHORIZATION NO : 308



AVCON, INC.
ENGINEERS & PLANNERS

5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL 32822-2779
OFFICE: (407) 599-1122 - FAX: (407) 599-1133

CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

Project Name:

NORTH DEVELOPMENT ROAD

Designer:	Checked by:
RP	RP
Technician:	ICE Proj. No.:
JP	23-024

Engineer of Record:

This item has been digitally signed and sealed by:



FLORIDA LICENSE NO, 45963

Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

PROFESSIONAL SEAL

Notes:	
110100.	

	REVISIONS				
No.	Description	Date	Ву		
Drawi	ng Name:				

UTILITY KEY PLAN


XXXXXXX

FAA A.I.P. Project No.:

FDOT Project No.:


XXXXX

sheet Number: UP-05



NOTES:

- SEE CITY OF OCALA STANDARD DETAILS FOR CONSTRUCTION DRAWING NUMBER SS-20E FOR ADDITIONAL REQUIREMENTS, CHEM TANK SOG, ODOR CONTROL SOG, ETC.
 *DRIVEWAY ELEVATIONS FROM MATCH EDGE OF PAVEMENT 12-FEET LEFT OF CENTERLINE TO THE 4.0-FOOT SWALE SHALL BE PER THE ROAD DESIGN AND TYPICAL CROSS SECTIONS PLUS 1.5-INCHES.





INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 ERTIFICATE OF AUTHORIZATION NO.: 308



AVCON, INC.
ENGINEERS & PLANNERS
5955 E. MICHGAN ST., SUITE 200 - ORLANDO, FL. 32822-2779
OFFICE: (407) 599-1122 - FAX: (407) 599-1133
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

NORTH DEVELOPMENT **ROAD**

Designer:	Checked by:	
RP	RP	
Technician:	ICE Proj. No.:	
.IP	23-024	

Digitally signed by Robert H



ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

e signature must be verified on any electronic PROFESSIONAL SEAL

	REVISIONS				
No.	Description	Date	Ву		
Drawing Na					
	LIFT STA	TION			

SITE PLAN

FAA A.I.P. Project No.:

FDOT Project No.:

XXXXX


heet Number: FEBRUARY 2024 **UP-06**



4" PVC FORCE MAIN 8" PVC SANITARY LINE 12" PVC WATER MAIN PCC PAVEMENT

→

FLOW DIRECTION



NOTES

- 1. WHERE ONE VALVE BOX EXTENSION IS REQUIRED USE STANDARD VALVE BOX EXTENSION.
- 2. WHERE MORE THAN ONE VALVE BOX EXTENSIONS ARE REQUIRED USE 6" D.I.P. CUT TO PROPER LENGTH SO VALVE BOX BOTTOM IS ONE CONTINUOUS SECTION.
- 3. VALVE BOX LID TO BE FURNISHED WITH THE WORD "WATER", FOR WATER MAIN INSTALLATION, "SEWER" FOR FORCE MAIN INSTALLATION, "REUSE" FOR REUSE MAIN INSTALLATION, OR "FIRE" FOR OEDICATED FIRE MAIN INSTALLATION.
- FOR ALL VALVES USE SOLID COMMON BRICKS LAID FLAT: ONE (1) BRICK FOR 2"-6" LINES; TWO (2) BRICKS FOR 8"-10" LINES; FOUR (4) BRICKS FOR 12" LINES OR LARGER.
- 5. 4"x 8" x16" SOLID PRECAST CONCRETE BLOCK TO BE INSTALLED UNDERNEATH VALVE BODY FOR SUPPORT
- 6. FLOWABLE FILL OR CONCRETE CAN BE USED IN LIEU OF LIMEROCK IF APPROVED BY THE ENGINEER.
- 7. FOR ALL VALVE BOXES INSTALLED IN PAVEMENT USE NON-POP LID.
- FOR ALL PRESSURE MAINS, TERMINATE LOCATING WIRE INSIDE VALVE BOX, SEE DETAIL G-15E.
- 9. PAINT LIDS IN BLUE FOR WATER; PURPLE FOR RECLAIM; GREEN FOR SEWER; RED FOR HYDRANT.



CITY OF OCALA STANDARD DETAILS FOR CONSTRUCTION

VALVE BOX INSTALLATION

IN ROADWAYS OR AREAS SUBJECT TO TRAFFIC REVISION DATE

G-13

CITY OF OCALA STANDARD DETAILS FOR CONSTRUCTION

B. PAINT BLUE "V" ON CURB FOR WATER VALVE LOCATION.

VALVE BOX COVER TO BE SET 1/8" - 1/4" ABOVE TOP OF CONCRETE COLLAR

...

NOTES

1. WHERE ONE VALVE BOX EXTENSION IS REQUIRED USE STANDARD VALVE BOX EXTENSIONS. 2. WHERE MORE THAN ONE VALVE BOX EXTENSIONS ARE REQUIRED USE 6" D.I.P. CUT TO PROPER LENGTH SO VALVE BOX BOTTOM IS CONTINUOUS SECTION.

3. VALVE BOX LID TO BE FURNISHED WITH THE WORD "WATER". FOR WATER MAIN INSTALLATION
"SEWER" FOR FORCE MAIN INSTALLATION. "REUSE" FOR REUSE MAIN INSTALLATION, OR "FIRE"
FOR DEDICATED FIRE MAIN INSTALLATION.

4. FOR ALL VALVES USE SOLID COMMON BRICKS LAID FLAT: ONE (1) BRICK FOR 2"-6" LINES; TWO (2) BRICKS FOR 8"-10" LINES; FOUR (4) BRICKS FOR 12" LINES OR LARGER.

6. FOR ALL PRESSURE MAINS, TERMINATE LOCATING WIRE INSIDE VALVE BOX, SEE DETAIL G-15E.

5. 4" x 8" x 16" SOLID PRECAST CONCRETE BLOCK TO BE INSTALLED UNDERNEATH VALVE BODY FOR SUPPORT.

7. PAINT LIDS IN BLUE FOR WATER; PURPLE FOR RECLAIM; GREEN FOR SEWER; RED FOR HYDRANT.

CONCRETE COLLAR 24" SQUARED OR 24" DIA. X 8" THICK W/ TWO #3 ROUND BARS EACH WAY

VALVE BOX SUPPORT (SEE NOTE 4)

- VALVE BOX LID TO BE PAINTED (SEE NOTE 7)

...


- FINISH GRADE

VALVE BOX TOP

VALVE BOX BOTTOM

- VALVE BODY SUPPORT

SECTION: GENERAL VALVE BOX G-14 INSTALLATION IN GRASS OR AREAS NOT SUBJECT TO TRAFFIC REVISION DAT



NOTES

- 1. MINIMUM RESTRAINED LENGTH SHALL BE ALWAYS 20 FEET.
- IN-LINE VALVES AND THROUGH RUN OF TEES OUTSIDE LIMITS OF RESTRAINED JOINTS FROM OTHER FITTINGS NEED NOT BE RESTRAINED UNLESS OTHERWISE INDICATED ON THE DRAWINGS.
- BRANCH VALVE RESTRAINED JOINT LENGTH SHALL BE AS SHOWN FOR PLUG, OR UNTIL PIPE TERMINATION, IF SHORTER.
- POLYETHYLENE ENCASED DIP, AND PVC PIPE RESTRAINED JOINT LENGTH SHALL BE 125% OF LENGTH SHOWN IN ABOVE TABLE.



CITY OF OCALA STANDARD DETAILS FOR CONSTRUCTION

RESTRAINED JOINT SYSTEM

PLUG

100

140

180

220

300

360

G-11



TINFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 RTIFICATE OF AUTHORIZATION NO.: 308



AVCON, INC.

NORTH DEVELOPMENT ROAD

hecked by: RP CE Proj. No.: 23-024

Engineer of Record:



Digitally signed by Robert H Palm Date: 2024.02.21 This time has been digitally signed and sinded by Rusert N. Pelin. P.E. on the case adjunct to the hard Present Copies of the document are not considered signed undiscided digital and calcular and the signature must be verified on any electrical copies.

-05'00'

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

	REVISIONS					
No.	Description	Date	Ву			
			1			
			1			
-			+			
+			+			
+			+			
			-			
			_			
			Т			
			1			
\neg		_	+			
Drawing Na			_			
Drawing Na	UTILITY DE					

FAA A.I.P. Project No.:


XXXXXX

FDOT Project No.:

XXXXX

Sheet Number FEBRUARY 2024

UP-07




- IN THE EVENT UNSTABLE OR UNSUITABLE BEDDING MATERIAL IS ENCOUNTERED AT OR BELOW THE LIMITS OF EXCAVATION NOTED ON THE DRAWINGS, SUCH MATERIAL SHALL BE REMOVED AND REPLACED WITH FILL APPROVED BY THE ENGINEER.
- UPPER LIMITS OF TRENCH EXCAVATION AND FOR CALCULATION OF UNSUITABLE MATERIAL REFERS TO ONE OF THE FOLLOWING CONDITIONS (REFER TO DETAILS G-17 & G-18):
- A. BOTTOM OF LIMEROCK BASE WHERE UNDER A PAVED ROADWAY EXCEPT WHERE A TWO FOOT (2) UNDERCUT BELOW THE ROADWAY BASE IS REQUIRED. SEE "B" BELOW.
- B. BOTTOM OF TWO FOOT (2) UNDERCUT BELOW THE ROADWAY SUBGRADE WHERE CALLED FOR IN THE CONTRACT DOCUMENTS.
- C. FINISH GRADE WHERE NOT UNDER A PAVED ROADWAY
- TYPICAL TRENCH SLOPES ARE 1:1 EXCEPT WHERE SOIL CONDITIONS WARRANT DEVIATIONS BUT SHALL BE SUBJECT TO THE DISCRETION OF THE ENGINEER OR THEIR REPRESENTATIVE. WHERE DEVIATION IS WARRANTED SLOPES ARE IN ACCORDANCE WITH 0.5.H.A. REQUIREMENTS. FOR PURPOSES OF CALCULATING, TRENCH SLOPES ARE ASSUMED TO BE 1:1 UNLESS OTHERWISE DIRECTED BY THE ENGINEER.
- IN DEEP CUTS, TRENCH SHORING OR A TRENCH BOX SHALL BE USED AS DIRECTED BY THE ENGINEER.



CITY OF OCALA STANDARD DETAILS FOR CONSTRUCTION

TRENCH EXCAVATION UNSUITABLE MATERIAL

G-16




- DENSITY TESTS TO BE TAKEN AT EACH 6" OF COMPACTED FILL, NOT LESS THAN 100 FEET (100') APART AS DIRECTED BY THE PROJECT ENGINEER, IN ACCORDANCE WITH F.D.O.T. MANUAL, LATEST REVISION.
- IF THE CONTRACTOR HAS COMPACTION EQUIPMENT WITH WHICH THE REQUIRED DENSITY CAN BE OBTAINED IN THICKER LIFTS THAN PERMITTED ABOVE AND UPON SATISFACTORY EVIDENCE THAT THE PROPOSED EQUIPMENT WILL PRODUCE WORK FOUNDLIN OUALITY TO THAT PRODUCED BY THE SPECIFIED METHODS. THE ENGINEER MAY PERMIT PLACEMENT OF A.A.S.H.T.O. GRANULAR MATERIAL SOIL GROUPS A-1, A-2, OR A-3 IN LIFTS UP TO A MAXIMUM OF 12" COMPACTED THICKNESS. THE CONTRACTOR WILL BE REQUIRED TO FURNISH EQUIPMENT AND LABOR TO EXCAVATE AND BACKFILL TEST PITS TO BE DUG FOR THE PERFORMANCE OF DENSITY TESTS.
- USE OF THICK LIFT COMPACTION PROCEDURES WILL NOT BE ALLOWED FOR THE FIRST STAGE BACKFILLING (BENEATH THE HAUNCHES) OF PIPE AND ON SIDES OF PIPE.
- REFER TO PROJECT PLANS AND SPECIFICATION, AND F.D.O.T. STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, UNSUITABLE MATERIAL FOR UNDERCUTTING REQUIREMENTS.
- 5. REFER TO PROJECT PLANS AND SPECIFICATIONS, AND F.D.O.T. STANDARD SPECIFICATIONS FOR ROAD REPLACEMENT
- TRENCH SHORING AND TRENCH BOXES SHALL BE UTILIZED PER O.S.H.A. REQUIREMENTS FOR TRENCH SAFETY, 29
 CFT 1926, SUBPART B.
- THE 2 FOOT (2) SUBGRADE UNDER LIMEROCK AND STABILIZED SUBGRADE BASES MUST BE CLEAN FILL WITH NO PLASTICS PRESENT.



CITY OF OCALA FOR CONSTRUCTION







TINFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 RTIFICATE OF AUTHORIZATION NO.: 308



AVCON, INC.

NORTH DEVELOPMENT ROAD

necked by: RP CE Proi. No.: 23-024

Engineer of Record:



Digitally signed by Robert H * Palm Date: 2024.02.21

This first has been digitally signed and staked by Riccer H Plain PE on the date adjusted to the sulf. Private misses of this discussed are to the discussed are to considered signed and the digitality must be entire to make the right production of the discussed and the digitality must be either considered assigned and the digitality must be either considered.

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

REVISIONS Description Date **UTILITY DETAILS**

(SHEET 2 OF 8)


FAA A.I.P. Project No.:

FDOT Project No.:

xxxxx

Sheet Number FEBRUARY 2024

UP-08




- 4. MANHOLE TO BE INSTALLED WITH 24" HINGED RING AND COVER.
- 5. FILL ANNULAR VOID BETWEEN PIPE AND RUBBER BOOT WITH GROUT AND FLUSH WITH MANHOLE WALLS.
- 6. EACH MANHOLE INSTALLED SHALL HAVE ONE COMPACTION DENSITY TEST AS SPECIFIED.
- 7. LIMEROCK WILL BE PLACED AROUND RING AND COVER TO BOTTOM OF ASPHALT.




CITY OF OCALA STANDARD DETAILS FOR CONSTRUCTION PRECAST CONCRETE **MANHOLE**

LESS THAN 5' DEPTH

SS-2





FOR CONSTRUCTION

STANDARD



TINFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 ERTIFICATE OF AUTHORIZATION NO.: 308



AVCON, INC.

ENGINEERS & PLANNERS
5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL 32822-2779
OFFICE: (407) 599-1122 - FAX: (407) 599-1133
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

NORTH DEVELOPMENT **ROAD**

hecked by: RP ICE Proj. No.: 23-024

Engineer of Record:



Digitally signed by Robert H Palm Date: 2024.02.21 This care has been digitally served and sealed by Resert H. Palin P.S. on the data adjaced in the most P. Most Capes of the indemnent on not considered served and other symbol.

The control of the cont

-05'00'

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

REVISIONS

UTILITY DETAILS

(SHEET 3 OF 8) FAA A.I.P. Project No.:


XXXXXXX

FDOT Project No.:

XXXXX

Sheet Number FEBRUARY 2024 UP-09

FOR CONSTRUCTION



FIELD-ERECTED WASTEWATER LIFT STATION NOTES:


1. CONSTRUCTION SHALL BE IN STRICT CONFORMANCE WITH CITY OF OCALA STANDARD SPECIFICATION SECTION 33 32 11 DATED 2/16/2023, OR MORE CURRENT EDITION, AND THESE DETAILS.


2. SUBMERSIBLE SOLIDS HANDLING WASTEWATER PUMPS AND COMPATIBLE EQUIPMENT SHALL BE MANUFACTURED BY:

A. SULZER
B. GRUNDFOS
C. FLYGT

E. APPROVED EQUAL ACCEPTIBLE TO CITY OF OCALA

3. SEE ENLARGED SITE PLAN FOR ADDITIONAL INFORMATION AND DIMENSIONS.







TINFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701



AVCON, INC. ENGINEERS & PLANNERS
5955 E. MICHIGAN 15, JUIE 200 - ORLAHOD, FL 32822-2779
FOFICE: (407) 599-1122 - FAX: (407) 599-1133
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057
www.wsooinlc.com

NORTH DEVELOPMENT **ROAD**

Designer:	Checked by:
Technician:	ICE Proj. No.:
JP	23-024

Engineer of Record:



Digitally signed by Robert H Palm 2024.02.21

This fern has been digitally spired and sevied by Robert N. Pilin, P.E. on the date adjacent to the least. Privide outpies of this document on roll considered skipner and sevied and the appalate month by explored the sevied and the spiral and sevied and sevied and the spiral and sevied and s -05'00'

> ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

REVISIONS

Date

Description

\vdash		 \rightarrow
\vdash		
		\neg
Drawing Nam	e:	

(SHEET 4 OF 8)


FAA A.I.P. Project No.:


XXXXXXX


FDOT Project No.:


FEBRUARY 2024

UP-10











INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 CERTIFICATE OF AUTHORIZATION NO.; 308



AVCON, INC.
ENGINEERS & PLANNERS
5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL. 32822-2779
OFFICE: (407) 599-1122 - FAX: (407) 599-1133
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

NORTH DEVELOPMENT **ROAD**

ICE Proj. No.: 23-024

Engineer of Record:



Digitally signed by Robert H * Palm Date: 2024.02.21

This item has seen digitally signed and sealed by Robert H. Phim. P.E. on the cathe absent to the seal. Priested copies of this decounted are not considered stayled and sealed and the separation Table Cathering on the medical conditions copies. -05'00'

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

REVISIONS

UTILITY DETAILS

(SHEET 5 OF 8)

FAA A.I.P. Project No.:


FDOT Project No.:


XXXXXXX

FEBRUARY 2024

UP-11

Water Main 10 ft. preferred 3 ft. minimum Water Main 12 inches preferred 6 inches minimum Water Main 12 inches is the minimum 2 inches is the minimum except for gravity sewer. Sanitary Sewer Force Main, Reclaimed Water (4) Water Main 12 inches is the minimum except for gravity sewer. then 6 inches is the minimum and 12 inches is minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum and 12 inches is minimum and 12 inches is minimum and 12 inches is minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum. Water Main 12 inches is the minimum except for gravity sewer. then 6 inches is the minimum except for gravity sewer. then 6 inches is the minimum. Water Main 12 inches is the minimum. Water Main 12 inches is the minimum. Water Main 12 inches is the minimum. Except for gravity sewer. The first form of the form of the first form of the form	Storm Sewer, tormwater Force Main, Reclaimed Water (2) Water Main 12 inches is the minimum and 12 inches is preferred 3 ft. minimum Water Main 12 inches is preferred 3 ft. minimum Water Main 12 inches is the minimum Valer Main	Other Pipe	Horizontal Separation	Crossings (1)	Joint Spacing @ Crossings (Full Joint Centered)
Water Main 10 ft. preferred 3 ft. minimum Water Main 12 inches preferred 6 inches minimum Water Main 12 inches is the minimum 2 inches is the minimum except for gravity sewer. Hen 6 inches is the minimum and 12 inches is minimum and 12 inches is the minimum and 12 inches is	Water Main Vacuum Sanitary Sewer 10 ft. preferred 12 inches preferred 12 inches preferred 12 inches preferred 13 ft. minimum 10 ft. preferred 12 inches preferred 12 inches preferred 13 ft. minimum 10 ft. preferred 12 inches preferred 12 inches preferred 13 ft. minimum 10 ft. preferred 14 inches preferred 15 inches preferred 15 inches preferred 16 ft. minimum 10 ft. minim	Stormwater Force Main,		12 inches is the minimum, except for storm sewer, then 6 inches is the minimum and	
Gravity or Pressure Sanitary Sewers Sanitary Sewer Force Main, Reclaimed Water (4) On-Site Sewage Treatment & Disposal System Water main should cross above other pipe. When water main must be below other pipe, the minimum separation is 12 inches. Reclaimed water regulated under Part III of Chapter 62-610, F.A.C. 3 Ft. for gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the of the gravity sanitary sewer.	Gravity or Pressure Sanitary Sewer Force Main, Reclaimed Water (4) On-Site Sewage Treatment & Disposal System Water main should cross above other pipe. When water main must be below other pipe, the minimum separation is 12 inches. Reclaimed water regulated under Part III of Chapter 62-610. F.A.C. 3 Ft. for gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the top of the gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the top of the gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the top of the gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the top of the gravity sanitary sewer. Reclaimed water not regulated under Part III of Chapter 62-610. F.A.C. Meer - This document is provided for your convenience only. refer to F.A.C. Rule 62-555.314 for additional construction meents. CITY OF OCALA SEPARATION OF	Vacuum Sanitary Sewer	10 ft. preferred	12 inches preferred	
Treatment & Disposal System Water main should cross above other pipe. When water main must be below other pipe, the minimum separation is 12 inches. Reclaimed water regulated under Part III of Chapter 62-610, F.A.C. 3 Ft. for gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the of the gravity sanitary sewer.	Treatment & Disposal System 10 ft. minimum System Water main should cross above other pipe. When water main must be below other pipe, the minimum separation is 12 inches. Rectained water regulated under Part III of Chapter 62-610, F.A.C. 3 Ft. for gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the top of the gravity sanitary sewer. Rectained water not regulated under Part III of Chapter 62-610, F.A.C. meer - This document is provided for your convenience only, refer to F.A.C. Rule 62-555.314 for additional construction ments. CITY OF OCALA SEPARATION OF	Sanitary Sewer, Sanitary Sewer Force Main, Reclaimed Water	10 ft. preferred	12 inches is the minimum, except for gravity sewer, then 6 inches is the minimum and 12 inches is	
separation is 12 inches. Reclaimed water regulated under Part III of Chapter 62-610, F.A.C. 3 Ft. for gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the of the gravity sanitary sewer.	separation is 12 inches. Reclaimed water regulated under Part III of Chapter 62-610, F.A.C. 3 Ft. for gravity sanitary sewer where the bottom of the water main is laid at least 6 inches above the top of the gravity sanitary sewer. Reclaimed water not regulated under Part III of Chapter 62-610, F.A.C. mer - This document is provided for your convenience only. refer to F.A.C. Rule 62-555.314 for additional construction ments. CITY OF OCALA SEPARATION OF	Treatment & Disposal	10 ft. minimum		
imer - This document is provided for your convenience only. refer to F.A.C. Rule 62-555.314 for additional construction mements.	CITY OF OCALA SEPARATION OF	separation is 12 inch Reclaimed water regul 3 Ft. for gravity sanior of the gravity sanior Reclaimed water not r	is. ated under Part III of Chapi ary sewer where the bottom y sewer. egulated under Part III of C	ter 62-610, F.A.C. of the water main is laid at le hapter 62-610, F.A.C.	





8" SERVICE LINE



TINFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 ERTIFICATE OF AUTHORIZATION NO.: 308



ENGINEERS & PLANNERS
5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL 32822-2779
OFFICE: (407) 599-1122 - FAX: (407) 599-1133
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

NORTH DEVELOPMENT **ROAD**

hecked by: RP RP ICE Proj. No.: 23-024



signed by Robert H Palm Date: 2024.02.21

-05'00'

ROBERT H. PALM, P.E.

REVISIONS

UTILITY DETAILS

(SHEET 6 OF 8) FAA A.I.P. Project No.:

XXXXXXX


FDOT Project No.:


XXXXX


UP-12

FEBRUARY 2024

Engineer of Record: Digitally This cam has been digitally signed and souled by Rozent H Pain, P.E. on the size adjacent to the Rozent H Pain, P.E. on the size adjacent to the size H. Priesed capies of this occupient are not considered signed unce useled start the upstate most to writing on any declarest cooper. FLORIDA LICENSE NO, 45963









INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 ERTIFICATE OF AUTHORIZATION NO.: 308



NORTH DEVELOPMENT **ROAD**

hecked by: RP ICE Proj. No.: 23-024

Engineer of Record:



Digitally signed by Robert H Palm Date: 2024.02.21

-05'00'

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

REVISIONS

Date

\Box			
\vdash			1
\vdash			\vdash
\vdash	 	-	-
\vdash			⊢
\perp	-		_
			П
			1
\vdash		_	-
_	 		_
Drawing	ITY DET	AILS	


(SHEET 7 OF 8)


FAA A.I.P. Project No.:

FDOT Project No.:

XXXXXX

Sheet Number: FEBRUARY 2024 UP-13





NOTE: ALL PIPING AND APPURTENANCES TO BE 2" FOR 8" AND BELOW WATER MAINS; 4" FOR 12" WATER MAINS; 8" FOR 16" WATER MAINS; 12" FOR 24" WATER MAINS. DOUBLE CHECK VALVE BACKFLOW PREVENTER TEST COCK (TYPICAL) THREADED NIPPLE (TYPICAL) GATE VALVE GATE VALVE PRESSURE GAUGE WITH VALVE (TYPICAL) 90° BEND (2 REQUIRED) - SAMPLING TAP 2" METER EXISTING MAIN 12-FT USE AT POINT(S) OF FILLING. ALL
OTHER LOCATIONS PROPOSED FOR
CONNECTION TO EXISTING MAINS MUST
REMAIN ISOLATED UNTIL F.D.E.P. USE VALVE BOX LOCK DEVICE OR MAINTAIN PHYSICAL SEPARATION UNTIL F.D.E.P. LETTER OR CLEARANCE IS RECIEVED LETTER IS OBTAINED. A TEMPORARY JUMPER CONNECTION IS REQUIRED AT ALL CONNECTIONS BETWEEN EXISTING ACTIVE WATER MAINS AND PROPOSED NEW WATER MAIN IMPROVEMENTS. TEMPORARY JUMPER WATER METERS WILL BE SUPPLIED BY THE CITY OF OCALA ORDINANCE SECTION 70-413. OF OCACA ORDINARACE SECTION 70-413.

2. THIS DETAIL IS TO BE USED FOR FILLING ANY NEW WATER MAIN OF ANY SIZE FOR EXISTING ACTIVE WATER MAINS AND FOR FULSHING OF NEW MAINS, AND FOR PULLING BACTERIOLOGICAL SAMPLES FROM ANY NEW WATER MAIN OF ANY SIZE. THE JUMPER CONNECTION SHALL BE MAINTAINED UNTIL AFTER FILLING, FLUSHING, TESTING, AND DISINFECTION OF THE NEW MAIN HAS BEEN SUCCESSFULLY COMPLETED AND CLEARANCE FOR USE FROM THE FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION (FDEP) HAS BEEN RECEIVED. THIS JUMPER CONNECTION SHALL ALSO BE USED TO MAINTAIN A MINIMUM PRESSURE OF 20 PSI IN THE NEW MAINS ALL THE TIME AFTER DISINFECTION AND UNTIL THE FORP CLEARANCE LETTER IS OBTAINED. ADEQUATE THRUST BLOCKING AND/OR RESTRAINTS SHALL BE PROVIDED TEMPORABLY, AS REQUIRED. PIPE MAD FITTINGS USED FOR CONNECTING THE WYPEP TO THE EXISTING PIPE SHALL BE DISINFECTED PRIOR TO INSTALLATION IN ACCORDANCE WITH AWAYA COSI, LATEST EDITION. THE TAPPING SLEEVE AND THE EXTERIOR OF THE MAIN TO BE TAPPED SHALL BE DISINFECTED BY SPRAYING OR SWABBING PER SECTION II OF AWWA COSI-LATEST. UPON RECEIPT OF CLEARANCE FOR USE FROM FDEP AND THE CITY OF OCALA, THE CONTRACTOR SHALL REMOVE THE TEMPORARY JUMPER CONNECTION. THE MAINS CAN NOW BE CONNECTED BY SLEEVE OR FLANGED CONNECTIONS. 4. ALL INSTALLATION AND MAINTENANCE OF THE TEMPORARY JUMPER CONNECTION AND ASSOCIATED BACK FLOW PREVENTION DEVICE, FITTINGS, VALVE, ETC., SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. 5. WATER FOR TESTING AND DISINFECTION OF THE NEW WATER MAIN AND WATER FOR MAINTENANCE OR OTHER USES SHALL BE AT THE CONTRACTORS EXPENSE. SECTION: WATER CITY OF OCALA TEMPORARY JUMPER STANDARD DETAILS W-30 CONNECTION FOR CONSTRUCTION



TINFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 RTIFICATE OF AUTHORIZATION NO.: 308



AVCON, INC.
ENGINEERS & PLANNES

555 E. MICHGAN ST., SUTE 500 - ORLANDO, FL 12822-2779
OFFICE: (407) 599-1122 - FAX: (407) 599-1123
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 505
www.avconinc.com

NORTH DEVELOPMENT ROAD

Designer:	Checked by:
RP	RP
Technician:	ICE Proj. No.:
JP	23-024



Digitally signed by Robert H Palm Date: 2024.02.21

The ten has been cighally signed and scaled by Rocert in Path, PE on the data adjacet to the seal. Preted course of the occurrent on old considered signed and sealed and the splatface must be verified on any detections. -05'00'

> ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

> > **REVISIONS**

No.	Description	Date	Ву
$\neg \top$			T
-			-
\rightarrow			₩
			1
		_	1
—			+-
_			
\neg			1
			-
\neg			1
			-
		1	
Drawing Na			_

UTILITY DETAILS (SHEET 8 OF 8)

FAA A.I.P. Project No.:

FDOT Project No.:

XXXXX

Date: Sheet Number: FEBRUARY 2024 **UP-14**



GENERAL NOTES:

SCHEFFAL NUTES:

It his hade routins information specific to the Federal and State guidelines and standards for the preparation of traffic control claus and for the execution of traffic control in work zones, for construction and mantenance peratrations and withly work on highways, reads and streets on the State Highway System. Certain requirements in this Index are based on the high volume nature of State Highway. For highways, coads and streets of the State Highway System, the local agency (City/County) having jurisdiction may adopt requirements based on the enummar requirements provided in the MITCD.

2. Use this Index in accordance with the Plans and Indexes 102-601 through 102-600. Indexes 102-601 through 102-600 are Operatment-specific typical applications of commonly encountered situations. Adjust device location or number thereof as recommended by the Ward-site Traffic Supervisor and approved by the Engineer. Devices include, but are not limited to, flaggers, portable temporary signals, signs, poweroen markings, and channelizing devices. Comply with MOTCD or applicable Department criterial for any Indexes and document the reason for the change.

		TABL	E 1	
CHA	NNELIZ	ING DE	EVICE SP	ACING
Work Zone Speed (mph)		Max.	Spacing (fee	t)
	Temi	es or orary Markers	Type II	Barricades. Barricades, lets, or Drum:
	Taper	Tangent	Taper	Tangent
≤ 45	25	50	25	50
≥ 50	25	50	50	100

	LE 2 NGTH "L"
Work Zone Speed (mph)	Min. Length (feet
≤ 40	$L = \frac{WS^2}{60}$
≥ 45	L = W5
	idth of offset ofeet need in mph

TABLE 4 BUFFER LENGTH "B"

Work Zone Min. Speed (mph) Length (feet


TABLE WORK ZONE SIG	
Road Type	Min. Spacing (feet)
ials and Collectors with Zone Speed ≤ 40 mph	200
ials and Collectors with Zone Speed ≥ 45 mph	500
ed Access Roadways "	1.500
	with work zone speed ± 55 y be reduced in accordance wed by the Engineer.

			⇒		
	-		⇒ D •		1
	andard acing	ļ.,	10 m		1000
		USINESS	40	Driveway	40
	EI	NTRANCE	Reduced	Driv	Reduced
11		_	Spacing		Spacing


For single business entrances, place one 24" x 36" business sign for each driveway entrance affected. Signs shall show specific business names. Logos may be promisted by business owners. Standard BUSINESS ENTRANCE sign in Index 700-102 may be used when approved by the Engineer.

4. Business entrance signs are intended to guide motorist to business entrances moved/modified or disturbed during construction projects. Business entrance signs are not required where there is minimal disruption to business driveways which is often the case with resurfacing type projects.

PLACEMENT OF BUSINESS ENTRANCE SIGNS AND CHANNELIZING DEVICES AT BUSINESS ENTRANCE



Entire Separator Shall Be



FIXED (SURFACE MOUNTED) CHANNELIZING DEVICES SECTION A-A

1. Temporary lane separators shall be supelemented with any of the following approved fixed (surface mountee) channelizing devices: temporary fuolular markers, vertical panels, or opposing traffic lane directly expenses (Act) shall only be used as center failed envilvers to separate opposing vehicular traffic and involvenc, too-way operation. Temporary Tubular Markers, Vertical Panels and Opposing Traffic Lane Divider panels shall not be intervalved within the limits where the temporary lane separator is used. The comercion between the channelizing device and the temporary lane separator curb shall hold the channelizing device in a vertical position.

Topered ends shall be used at the beginning and end of each run of the temporary lane separator to form a
gradual increase in height from the pavement level to the top of the temporary lane separator.

5. The Contractor has the option of using partable temporary lane separators containing fixed channelizing devices in lieu of the temporary asphalt separator and channelizing devices detailed on this sheet. The partable temporary lane separator shall come in partable sections that can be connected to martial nontinious alignment between the separator curb sections. Each temporary lane separator section shall be 36 inches to 48 inches in Italy length. Partable temporary lane separators shall displace the color of the pavement marking. Portable temporary tane separators shall be one of those listed on the Approved Products List.

GENERAL INFORMATION FOR TRAFFIC CONTROL THROUGH WORK ZONES



INDEX

Engineer of Record:

Digitally signed by Robert H Palm 2024.02.21

hecked by: RP

ICE Proj. No.:

23-024

This time has been digitally signed and sailed by Rabert N. Peter, P.E. on the date adjusted to the scale Printed occurs of the Southers are not considered signed and sailed and the significant formula be written on any electricity copies. -05'00'

TINFRASTRUCTURE

CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701

AVCON

AVCON, INC.

ENGINEERS & PLANNERS
5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL 32822-2779
OFFICE: (407) 599-1122 - FAX: (407) 599-1133
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

NORTH DEVELOPMENT

ROAD

CERTIFICATE OF AUTHORIZATION NO.: 3

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

REVISIONS Description Date

FDOT STANDARD DETAILS (SHEET 1 OF 2)

FAA A.I.P. Project No.:

XXXXXXX

FDOT Project No.:

Sheet Number: FEBRUARY 2024

GENERAL INFORMATION FOR TRAFFIC CONTROL THROUGH WORK ZONES FDOT STANDARD PLANS 11/01/20 102-600 1 of 11 8 10 12 8 10 12 A-FRAME POST MOUNT DIRECTION INDICATOR
BARRICADE

FY 2023-24

CHANNELIZING DEVICES

VERTICAL PANEL

SHEET

SHEET

11/01/20

PEDESTRIAN LONGITUDINAL CHANNELIZING DEVICES TEMPORARY BARRIER NOTES: Where a barrier is specified, any of the types below may be used in accordance with the applicable Index: Traiter Mounted Barriers may be used to provide positive protection for workers within the work areas, APL drawings may be used as a guide to develop project specific Temporary Traffic Control Plans that are signed and sealed by the Contractor's Engineer.

MULTILANE ROADWAY SHOWN, TWO-LANE ROADWAY SIMILAR

FY 2023-24

FDOT STANDARD PLANS

NOTES: This Index applies to Two-Lane, Two-Way and Multilane Roadways, including Medians of divided roadways, with work beyond the shoulder.

2. Use Index 102-602 when the work operation texcluding establishing

3. Use Index 102-660 when Work Area encroaches a Sidewalk.

SYMBOLS:

Work Area

Lane Identification and Direction of Traffic

9. For pedestrian longitudinal channelizing devices, the device shall have a minimum of 8° continuous detectable edding above the walking. A gap out exceeding a beight of 1s allowed to facilitate drainage. The Lap surface of the device shall be a minimum height of 32° and have a ½° or less difference in any plane at all connection points between the devices to facilitate hand trailing. The bottom and the top surface of the device shall be in the same vertical plane. If pedestrian deportly protection is require the device shall be in the same vertical plane. If pedestrian deportly protection is required the device shall be in the same vertical plane. If pedestrian deportly protection is required the device shall be in the same vertical plane. If pedestrian deportly protection is required to exceed the control of the protection of the device shall be in the same vertical plane. If pedestrian deportly protection is required to a same protection of the pro FY 2023-24 GENERAL INFORMATION FOR TRAFFIC CONTROL THROUGH WORK ZONES INDEX STANDARD PLANS 102-600 10 of 11

FY 2023-24 REVISION 11/01/20 STANDARD PLANS TWO-LANE AND MULTILANE ROADWAY, WORK BEYOND THE SHOULDER

INDEX 102-601 1 of 1

UP-15



11/01/20

CHANNELIZING DEVICE NOTES:

1. The details shown on this sheet are for the following purposes:

a. For ease of identification and
b. To provide information that supplements or supersedes that provided by the MUTCO. The Type III Barricade shall have a unit length of 6-0° only. When barricades of greater lengths are required those lengths shall be in multiples of the 6-0° unit.


No sign panel should be mounted on any chamelizing device unless the channelizing device/sign combination was found to be crashworthy and the sign panel is assumed in accordance with the vendor drawing for the channelizing device shown on the Approved Products List (APL).


4. Ballast shall not be placed on top rails or any striped rails or higher than 13' above

5. The direction indicator barricade may be used in tapers and transitions where specific directional guidance to drivers is necessary. If used, direction indicator barricades small be used in series to direct the driver through the transition and into the intended travel lane.

6. The splicing of sheeting is not permitted on channelizing devices or MOT signs.

7. For rails less than 3-0" long, 4" stripes shall be used. 8. Cones shall:
b. Be used only in active work zones where workers are present,
b. Be reflectorized as per the MUTCD with Department-approved reflective collars when used at night.







INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 CERTIFICATE OF AUTHORIZATION NO.: 3086



AVCON, INC.
ENGINEERS & PLANNERS
5.5. MICHIGAN ST. SUITE 200 - ORI ANDO EL 32822-22

roinct Name:

NORTH DEVELOPMENT ROAD

Designer:	Checked by:
Technician:	ICE Proj. No.:
MT	23-024

Engineer of Record:

INDEX

102-613

1 of 5



Digitally signed by Robert H Palm Date: 2024.02.21

there has been digitally signed and seeled by art H. Pathr. PE on the date adjacent to the Periodic loudies of the distributed are not distributed as post of every distributed as post of every distributed as not dis not distributed as not distributed as not distributed as not di

ROBERT H. PALM, P.E. FLORIDA LICENSE NO, 45963

R	E٧	ISI)	0	NS
ĸ	ΕV	1151	U	NS

140.	Description	Date	- Dy
			${}^{+}$
-			+
			\perp
			Т
	-		
			\top
			Т
	-		\top

FDOT STANDARD DETAILS (SHEET 2 OF 2)


FAA A.I.P. Project No.:

XXXXXXX

FDOT Project No.:

XXXXX

Date: Sheet Number: FEBRUARY 2024 UP-16





TINFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115



AVCON, INC.

NORTH DEVELOPMENT ROAD

Designer:	Checked by:	
RP	RP	
Technician:	ICE Proj. No.:	
ID	22.02	

Engineer of Record:

No.45963 : Palm STATE OF Date:

Digitally signed CENS by Robert H LORIDA 2024.03.18 14:43:58 -04'00'

ROBERT H PALM P.F. FLORIDA LICENSE NO, 45963

PROFESSIONAL SEAL

REVISIONS

140.	Doscription	Dute	٠,
$\neg \vdash$			
		_	1
-			_
		_	\vdash
\neg		_	1
		\vdash	
\neg			
		_	
		_	
Drawing Nar	ne:		

LIFT STATION DETAILS


XXXXXXX

FDOT Project No.: XXXXX

Sheet Number:

FEBRUARY 2024

UP-17




NOTE:

1. SIZE AND NUMBER OF DUCTS SHALL BE PER OCALA ELECTRIC REQUIREMENTS.

ELECTRICAL DUCT INSTALLATION

N.T.S.



ELECTRICAL DUCT INSTALLATION



INFRASTRUCTURE CONSULTING & ENGINEERING

5550 WEST IDLEWILD AVE. SUITE 115 TAMPA, FLORIDA 33634 (813) 330-2701 RTIFICATE OF AUTHORIZATION NO.: 308



AVCON, INC.
ENGINEERS & PLANNERS
5555 E. MICHIGAN ST., SUITE 200 - ORLANDO, FL. 32822-2779
OFFICE: (407) 590-1122 - FAX: (407) 590-1133
CORPORATE CERTIFICATE OF AUTHORIZATION NUMBER: 5057

NORTH DEVELOPMENT **ROAD**

hecked by: SD SD ICE Proj. No.: EH 23-024

Engineer of Record:



Digitally signed by Sean Day Date: 2024.02.21 15:50:23-05'00'

SEAN DAY, P.E. FLORIDA LICENSE NO, 80296

	REVISIO	ONS	
No.	Description	Date	Ву
			$\overline{}$
_			1
\neg			1
_		_	+-
_			+
		_	+-
Drawing Na	ame:		
	INSTALLA	TION	
	DETAIL		

FAA A.I.P. Project No.:

FDOT Project No.:

XXXXX

FEBRUARY 2024

Sheet Number: EL-02